

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records, Vol. 19 Page 7886)

-----  
Set post 4x5" dia., 5 ft. long, 18" ground for ¼ sec. cor. from which

A Fir, 12" dia., bears N.31°W., 40 lks.

A Pine, 14" dia., bears S.38°W., 37 lks.

BLM dependent resurvey by Daniel E. Weller, Cadastral Surveyor, under Group #1884, surveyed July/Sept 1998. (DCSO records Vol. 53 Page(s) 20482)

-----  
Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance. There is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, and brass cap mkd. T 31 S R 5 W

1/4  $\frac{S}{S}$   $\frac{6}{7}$

1998

from which

A fir, 11" dia., bears N.57½°E., 46 lks., mkd. ¼ S6 BT.

A fir, 11" dia., bears S.30 ¾°E., 50½ lks., mkd. X BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.