

PRIMARY CORNER DESCRIPTION So. Sec. Cor. for 31 and 32 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7884)

Set post cor. to secs. 5, 6, 31 and 32, from which
 A Cedar 8" dia., bears S.22°30'E., 7 lks. dist.
 A Laurel 8" dia., bears N.83°30'W., 32 lks. dist.
 A Fir 5" dia., bears S.22°W., 23 lks. dist.
 A Fir 4" dia., bears N.50°E., 6 lks. dist.

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8610)

Intersect N. bdy. of Tp., 74 lks. E. of cor. of secs. 5, 6, 31, and 32, which having disappeared, I replace by setting a yew post, 3 ft. long, 4" sq., 24" in the ground, for cor. of secs. 5,6, 31 and 32, marked T31S S32 on NE., R5W S5 on SE.; T32S S6 on SW.; and S31 on NW. faces; with 5 notches on E. and 1 notch on W. edges, from which
 A Dogwood 8" dia., bears S.10°W. 17 lks mkd T32S R5W S6 BT
 A Dogwood 6" dia., bears N.8°W. 45 lks mkd T31S R5W S31 BT
 The other bearing trees are standing and as described by the surveyor general. I DESTROYED all marks referring to secs. 5 and 6.

BLM resurvey by Joseph Gawron and Norman McDonald under Group #472, surveyed June/July 1962 (DCSO records Vol. 32 Page(s) 13246)

The cor. of secs. 31 and 32, determined from the remains of an original bearing tree:
 A down Cedar 12" dia., bears S.22½°E., 7 lks. dist., with a burned face, mkd. BT.
 At the corner point
 Set an iron post, 30 ins. long, 2½ ins. dia., 26 ins. in the ground, with brass cap mkd: T 31 S R 5 W
 S 31 | S 32
 S 6
 T 32 S
 1962

from which
 A Fir 6" dia., bears N.84½°E., 87 lks. dist., marked T31S R5W S32 BT.
 A Fir 6" dia., bears N.38½°W., 66 lks. dist., marked T31S R5W S31 BT.

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Cor Secs 31 & 32, only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Lloyd "David" Smith - For: State of Oregon, Dept. of Forestry
- June 1998 - M 129-8

Found - BLM 2½"x30" iron pipe with brass cap. 1962
8" Cedar, S.22½°E., 7 lks., now 14"x1' high rotten
stump, face missing, axe work visible. 1855
6" Fir, N.84½°E., 87 lks., now 15", face closed.
1962
6" Fir, N.38½°W., 66 lks., now 9", face closed. 1962
Re-witnessed -
Orange carsonite marker CBM-250 labeled witness post
N.61°E., 3.10' to base.
Orange carsonite marker CBM-250 labeled witness post
N.74°W., 3.60' to base.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2883, surveyed March 2018/April
2018 - (DCSO records Vol. 59 Page(s) 23927-28)

The cor. of secs. 31 and 32 only, on the S. bdy. of the Tp.,
perpetuated by Smith, in 1998; monumented with an iron post,
2½" dia., firmly set, projecting 3" above ground, with a
brass cap (properly) mkd.
from which the remains of an original bearing tree
A sawed decayed cedar stump, 12" dia., bears S.22½°E., 4.6
ft., no marks visible.
and the remains of the bearing trees mkd. by Gawron and
McDonald in 1962
A fir, 20" dia., bears N.84½°E., 57.4 ft., with a healed
blaze.
A decayed fir snag, 9" dia., bears N.38½°W., 43.6 ft.,
with a healed blaze.
and a new bearing tree
A fir, 12" dia., bears N.55½°W., 35.0 ft., mkd. T31S R5W
S31 BT.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at
the base right side-center & each monument established or
remonumented has a magnet deposited in a white plastic case
at the base of the stainless steel post. Alum. Angle iron
driven alongside each monument.
Corner is located on a gentle SE slope.
Latitude 42°49'33.25"N. Longitude 123°19'38.12"W.
NAD 1983 (2011)