

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7930)

-----  
Marked a Sugar Pine 36" dia., ¼ S on W. side for the ¼ sec. cor., from which

A Fir 22" dia., bears S.45°E., 3 lks. dist., mkd. ¼ S BT.

A Dogwood 6" dia., bears N.30°W., 16 lks. mkd. ¼ S BT.

Survey by Arnold G. Gibson, Oregon State Board of Forestry - Wit: D.Bagger; R. Schulson; H.B. Baughn - Aug. 1963 - C.S. File 51/264

-----  
Found - Orig. 36" Sugar Pine (cor. tree), now 42" stump, cut low, from which a 22" Fir bears S.45°E., 3 lks., now 32" stump, in place, burnt and rotted.

6" Dogwood bears N.30°W., 16 lks., burnt roots in ground.

3 link Cr., SE, North 7.00 chains; in place. Line blazes N and S.

Set 1½" x 36" Galv. Iron pipe as reference monument, N.16°E., 2.1 ft. from cor. point in center of Pine stump with 3" cap mkd: "Ore.St.Bd.of Forestry RM 2.1 ft. 1963 RS 359" 30" in ground, from which a

5" Fir bears N.31°E., 23.8 ft. scribed ¼ S32 BT.

15" Fir bears N.75½°W., 54.0 ft. scribed ¼ S31 BT RS 359.

Set 4"x4"x72" white painted Cedar post 2.0 ft. East of corner pipe. OSFD metal location poster on 15" Fir BT.

Lloyd "David" Smith - For: State of Oregon, Dept. of Forestry - June 1998 - M 129-8

-----  
Found - 36" Sugar Pine, Orig. corner tree, now 36"x1' high very rotten stump. 1882

Oregon St. Board of Forestry 1½"x36" gal. IP w/3" bronze cap, reference mon., N.16°E., 2.1'. 1963

22" Fir, S.45°E., 3 lks., now 22"x2' high rotten stump in place, axe work visible. 1882

5" Fir, N.31°E., 23.8', now 12", face closed. 1963

15" Fir, N.75½°W., 54.0', yellow metal location poster, now 23" in place, face closed, yellow metal location poster. 1963

4"x4"x72" White painted Cedar post, East 2.0', now N.70°E., 3.7'.

Re-witnessed -

10" Fir, S.31°W., 11.5' to aluminum nail in BT face scribed "¼ S31 BT", BT tag. (Cont. next page)

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" Fir, S.4°E., 12.0' to aluminum nail in BT face  
scribed "¼ S32 BT", BT tag.  
Distances measured to OSBF reference monument.

Fd BTs as per M129-8 by David Edwards - March 2015 - M169-18

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2883, surveyed March 2018/April 2018 - (DCSO records Vol. 59 Page(s) 23927-28)

-----

The ¼ sec. cor. of secs. 31 and 32, perpetuated by Gibson, in 1963; subsequently perpetuated by Smith, in 1998; monumented with the remains of the original cor. tree, a heavily decayed pine stump, 36" dia., with no marks visible, from which the remains of an original bearing tree

A sawed, decayed fir stump, 36" dia., bears S.45°E., 4.3 ft., no marks visible. (Record, 2.0 ft.)  
and the accessories mkd. by Gibson

An iron post, 2½" dia., firmly set, projecting 12" above ground, bears N.19°31'47"E., 2.10 ft., with a brass cap mkd. OREGON STATE BOARD OF FORESTRY RS 239 2.1 RM 1963 X and an arrow pointing to the cor.

A fir, 14" dia., bears N.30°E., 23.7 ft., with a healed blaze.

A fir, 26" dia., bears N.76¾°W., 53.8 ft., with a healed blaze.

and the bearing trees mkd. by Smith.

A fir, 10" dia., bears S.11°E., 10.5 ft., with a healed blaze.

A fir, 13" dia., bears S.30°W., 9.6 ft., with a healed blaze.

At the corner point  
Set a stainless steel post, 28 ins. long, 2½" dia., in the center of the decayed stump, 27" in the ground, with brass cap mkd.

T31S R 5 W  
¼  
S 31 | S 32  
2018

Corner is located on a broken NE slope.