

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Paage 7933)

-----  
Set a stone, 12x12x8 ins. for the cor. to secs. 19, 20, 29 and 30, marked with two notches on S. and five notches on the East angles of the same, from which

- A Fir 20" dia., bears N.80°E., 25 lks. dist., marked T31S R5W S20 BT.
- A Fir 24" dia., bears S.30°E., 35 lks. dist., marked T31S R5W S29 BT.
- A Yew 10" dia., bears S.40°W., 55 lks. dist., marked T31S R5W S30 BT.
- A Fir 44" dia., bears N.24°W., 64 lks. dist., marked T31S R5W S10 BT.

BLM resurvey by James Jelley and Wayne Rogers under Group #1101, surveyed Sept. 1982-May 1983 (DCSO records Vol. 45 Page(s) 17491-92)

-----  
Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an alum. post, 28 ins. long, 2½ ins. dia., 22 ins. in the ground, with alum. cap mkd:

T 31 S R 5 W  
S 19 S 20  
S 30 S 29  
1982

from which

- A Fir 7" dia., bears N.29½°E., 159 lks. dist., mkd. T31S R5W S20 BT.
- A Fir 4" dia., bears S.88°E., 77 lks. dist., mkd. X BT.
- A Fir 14" dia., bears S.25°W., 16 lks. dist., mkd. T31S R5W S30 BT.
- A Fir 6" dia., bears N.15°W., 33 lks. dist., mkd. T31S R5W S19 BT.

Fd. OK by Bruce Shaner, May 1993, C.S. File 63/149 & M 116-64