

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7936)

-----  
Marked a Fir, 12" dia.,  $\frac{1}{4}$  S on W. side, for the  $\frac{1}{4}$  sec. cor., from which

A Fir 18" dia., bears S.16°E., 22 lks. marked  $\frac{1}{4}$  S BT.

A Fir 36" dia., bears West, 23 lks. marked  $\frac{1}{4}$  S BT.

BLM resurvey by James Jelley and Wayne Rogers under Contract #1101, surveyed Sept. 1982/May 1983 (DCSO records Vol. 45 Page(s) 17494)

-----  
Point for the  $\frac{1}{4}$  sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an alum. post, 28 ins. long,  $2\frac{1}{2}$  ins. dia., 24 ins. in the ground, with alum. cap mkd: T 31 S R 5 W

$\frac{1}{4}$   
S 19 S 20  
1982

from which

A Fir 12" dia., bears N.36°E., 10 lks. dist., mkd.  $\frac{1}{4}$  S20 BT.

A Grand Fir 12" dia., bears N.53°W.,  $10\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S19 BT.

(From this point, United States Coast and Geodetic Survey triangulation station SILVER BUTTE 1942 bears S.85°57'W., 209.94 chs. dist.)