

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7936)

Set a Cedar post, 4 ft. long, 4" diam., 20" in ground for the cor. to secs. 17, 18, 19 and 20, marked T31S R5W S17 on NE. face, S20 on SE face, S19 on SW. face and S18 on NW. face, also 3 notches on South and 5 notches on East angles of same, from which

- A Fir 14" dia., bears N.18°E., 33 lks. dist. marked T31S R5W S17 BT.
- A Fir 12" dia., bears S.10°E., 34 lks. dist. marked T31S R5W S20 BT.
- A Fir 13" dia., bears S.25°W., 41 lks. dist. marked T31S R5W S19 BT.
- A Fir 14" dia., bears N.68°W., 23 lks. dist. marked T31S R5W S18 BT.

Survey by Victor S. King - Wit: Chester Jones - For: Bate Lumber Co. - Feb. 5, 1959 C.S. File 42/425-6

Found - Orig. BT, 36" Fir N.68°W., 23 lks. with scribing visible. (I rescribed this corner in the bark)

Set 1" steel reinforcing rod 36" long, 30" in ground, from which I set the following new bearing trees:

- 7" W.Fir S.72°E., 13.4 ft. scribed T31S R5W S20 BT.
- 9" W.Fir S.24°W., 29.6 ft. scribed T31S R5W S19 BT.
- 12" W.Fir N.40°W., 6.9 ft. scribed T31S R5W S18 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones and Joe Brady - May/June 1966 - C.S. File 54/25-28

Found - 1" Iron rod at corner.
Orig. 36" D.Fir N.68°W., 15.2 ft., opened for scribe, non visible, bark scribe "BT".

12" W.Fir now 14", N.40°W. 6.9 ft. opened for scribe "31" visible.

- 7" W.Fir now 9", S.72°E., 13.4 ft. good scar.
- 9" W.Fir S.24°W., 29.6 ft., Tree down.

New BTs - 14" W.Fir, S.86°W., 37.6 ft. scribed ¼ S19 CS BT.
8" W.Fir N.51°E., 41.4 ft. scribed ¼ S17 CS BT.

BLM Corrective Resurvey - John Jelley, Lynn Roseberry, Floyd Brooks, Under Group #s 320 and 614, - Surveyed June 1966 through May 1968. (DCSO records Vol. 35 Page(s) 14374-75)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

The Sec. Cor. perpetuated and recorded by King in 1959, monumented with a steel rod, 1" dia., protruding 6" above ground, firmly set, from which the remaining original bearing tree:

A Fir 38" dia., bears N.18°E., 33 lks. dist., with scribe mark B visible on opened blaze. Remarked T31S R5W S17 BT RS 442 on bark, by King, in 1959 and bearing trees mkd. by King in 1959

A White Fir 9" dia., bears S.72°E., 19½ lks. dist., with illegible scribe marks visible on open blaze.

A White Fir 14" dia., bears N.40°W., 10 lks. dist., with illegible scribe marks visible on open blaze. and bearing trees mkd. by Powell in 1966

A White Fir 8" dia., bears N.51°E., 63 lks. dist., with scribe marks T31S R5W S17 CS BT visible on open blaze.

A White Fir 14" dia., bears S.83°W., 56½ lks. dist., with scribe marks T31S R5W S19 CS BT visible on open blaze.

At the Corner point

Set an iron post, 28 ins. long, 2½ ins. dia., 22 ins. in the ground, directly over the steel rod, with brass cap mkd:

T 31 S R 5 W
 S 18 | S 17
 S 19 | S 20
 1966

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - S.J. Flause, Wit. - Feb. 5, 1981 - C.S. File 61/19-4

Found - 1966 BLM brass cap on a 2½" I.P., firmly set and protruding 10" above ground, properly marked.

An orig. 14" now a 36" DBH D.Fir bears N.18°E., 21.8 ft. This tree has evidence of an opened and now rehealed blaze and is bark scribed RS 442 S17 BT.

A search is made for other orig. BTs, none are found
 A 7" now a 12" DBH W.Fir bears S.72°E., 12.8 ft. (Rec. 13.4 ft.) Tree has healed single blaze and bark scribing RS 442.

No evidence of 9" W.Fir is found.

A 12" now an 18" DBH W.Fir bears N.40°W., 6.9 ft. Tree has fully healed single blaze, bark scribing RS 442 is visible.

A 14" now an 18" DBH W.Fir bears S.86°W., 37.0 ft. (Rec. 37.6 ft.) Tree has partially healed upper blaze and a fully healed lower blaze. The upper blaze is opened and found to read as recorded in 1966 BLM notes. Notes by Powell in 1966 record both bearing tree scribings incorrectly as reading "¼ S ----". (Cont. Next Page)

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An 8" now a 10" DBH W.Fir bears N.51°E., 40.8 ft.
(Rec. 41.4 ft.) Tree has a well healed double
blaze.
Monument location is accepted and all bearing trees are
tagged with DCSO BT tags. Tags are marked with bearings and
distances measured as recorded in this visit.

Cor.FD. OK by BLM survey, James Jelley and Wayne Rogers,
1982-83 (DCSO records, Vol. 45 Pages 17494-95)