

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. to Sections 7, 8, 17 & 18.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records, Vol. 19 Pages 7885 & (Vol.33 Pg. 13667, duplicate)

Set post 5 x 5 ins, dia. 4 ft. long in mound of rock for corner. No witness trees, nothing suitable to mark. This post is on the side of a Mt. sloping south.

B.L.M. Resurvey - John M. Jelley, Lynn M Roseberry, Floyd A Brooks, under Group #s 314 & 620, surveyed, June 1966 through May 1968. (DCSO records Vol. 35, Pg.14375)

Set at proportionate distance, an iron post, 28" long 2½" dia. 24" in ground with brass cap marked: T 31 S R 5 W

S 7	S8
S18	S17
1966	

from which

- A Live Oak, 7" dia. bears N.84°E., 23½ lks. dist. marked:
T31S R5W S8 BT
- A Live Oak, 7" dia. bears S.23°E., 33 lks. dist. marked:
T31S R5W S17 BT
- A Fir, 33" dia. bears S.42°W., 47 lks. dist. marked:
T31S R5W S18 BT
- A Fir, 23" dia. bears N.25°W., 48 lks. dist. marked:
T31S R5W S17 BT

Fd. Ok 2/2020 - R. Quimby - C.S. File 65/104-63