

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. P. Wright under contract #281 dated May 16, 1878 (DCSO records Vol. 19 Page(s) 7888)

Set post 5x5 ins. dia., 3½ ft. long, 18" in ground, steep hill side for ¼ sec. cor., from which
A Live Oak 5" dia., N.59°E., 30 lks. dist.
A Madrona 3" dia., N.67°W., 20 lks. dist.

Arthur R Evans, R.E. #2741 - Wit: Glen Murdock & Milo Godfrey - Feb. 16 & Mar. 11, 1955 - C.S. File 41/367-2 & M 12-15

Found - Orig. Live Oak now 10", N.59°E., 30 lks. I cut into this. In good shape.
Orig. Madrone now 12", N.67°W., 20 lks. In good shape.
Set a 3" x 3" x 48" Fir stake for corner.
Blaze and scribe new BT:
16" D.Fir S.32½°E., 44.8 ft. (dist. to center) marked ¼ S 5 BT. Copper tag, R.E. 2741.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones and Terry Connell - June 1966 - C.S. File 54/25-13

Found - Scribed stake mkd. ¼ S6 - ¼ S5.
12" Laurel now 15", N.67°W., 13.2 ft., bark scribe visible.
16" D.Fir now 19", S.32½°E., 44.8 ft. shows good scar.
10" Live Oak N.59°E., 19.8 ft. Had been opened, no scribe visible.
Set brass cap at cor. mkd: County Surveyors Office
T 31 S R 5 W
¼ S 6 | S 5
1966
Reblazed and rescribed:
15" Laurel N.67°W., 13.2 ft. mkd. ¼ S6 CS BT.
This corner lies on small spur about 80.0 ft. North of rocky ravine.

Ron Quimby - For: Cow Creek Indians 6/2016 - M171-12 A&B

Found - 1966 DCSO Brass cap
16" madrone N.67°W., 13.2' with visible scribe.
28" D.Fir S.32½°E., 44.8' with good scar.
10" downed Oak N.59°E., 19.8'
New - 4" D.Fir S.51°W., 22.8' scribed "¼ S6 BT"
8" Cedar N.04°E., 43.8' scribed "¼ S5 BT"