

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7934)

Set a Fir post, 3 ft. long, 3" square, 18" in ground for the ¼ sec. cor., marked ¼ S on the N. face, from which
A Fir 15" dia., bears N.65°E., 15 lks. marked ¼ S BT.
A Fir 44" dia., bears S.42°W., 13 lks. marked ¼ S BT.

BLM resurvey by James Jelley and Wayne Rogers under Contract #1101, surveyed Sept. 1982/May 1983 (DCSO records Vol. 45 Page(s) 17491)

Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an alum. post, 28 ins. long, 2½ ins. dia., 12 ins. in ground to bedrock, in a mound of stone, 3 ft. base, top top, with alum. cap mkd: T 31 S R 5 W

¼ S 20
S 29
1982

from which

A Grand Fir 13" dia., bears N.3¼°E., 22 lks. dist., marked ¼ S20 BT.

A Grand Fir 13" dia., bears S.14°W., 14 lks. dist., marked ¼ S29 BT.