

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7937)

Set a Laurel post, 3 ft. long, 3" square, 18" in ground for the 1/4 sec. cor., marked 1/4 S on the N. side, from which
A Laurel 12" dia., bears N.35°E., 22 lks. mkd. 1/4 S BT.
A Chinquapin 10" dia, bears S.35°W., 22 lks. mkd. 1/4 SBT

BLM resurvey by James Jelley and Wayne Rogers under Contract #1101, surveyed, Sept. 1982/May 1983 (DCSO records Vol. 45 Page(s) 17495-96)

Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an alum. post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with alum. cap mkd: T 31 S R 5 W

1/4 S 17
S 20
1982

from which

A Fir 23" dia., bears N.68 3/4°E., 64 lks. dist. marked 1/4 S17 BT.

A Fir 7" dia., bears S.7 1/2°E., 17 lks. dist., marked 1/4 S20 BT.