

PRIMARY CORNER DESCRIPTION 1/4 Corner to Sections 8 & 17.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records, Vol. 19 Page 7940)

Set a Fir post, 3 ft. long 3 ins. sq., 18" in ground for the ¼ corner, mkd: ¼ S on N face, from which:

A Yew, 7" dia. bears S.45°W., 19 lks. dist. mkd: ¼ S BT.

A Fir, 13" dia. bears N.17°W., 64 lks. dist. mkd: ¼ S BT.

B.L.M. Resurvey - John M. Jelley, Lynn M Roseberry, Floyd A Brooks, under Group #s 320 & 614, surveyed, June 1966 through May 1968. (DCSO records Vol. 35, Pg.14376-77)

Set at proportionate distance, an iron post 28" long, 2½" dia. 24" in ground marked: T31S R5W

$\frac{1}{4}$ $\frac{S\ 8}{S\ 17}$
1966

New Accessories -

A Fir, 30" dia. bears N.38°E., 34 lks. marked ¼ S8 BT.

A Fir, 30" dia. bears S.85°E., 40 lks. marked ¼ S17 BT.

Ron Quimby - Crew: N. Fromdahl & L. Heddens - 2/2020 - C.S.
File 65/104-46

Found - BLM brass cap (properly mkd)

33" Fir N.38°E., 22.4 ft.

34" Fir S.85°E., 26.4 ft.

New - 16" Fir S.28°W., 41.5 ft. scribed ¼ S17 BT.

22" Fir S.26°E., 72.5 ft. scribed ¼ S17 BT.

Note - Area badly burnt 2019

Compass decl. 15½°E.