

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.P. Wright under Contract #281 dated May 16, 1878
(DCSO records Vol. 19 Page(s) 7888)

Set ¼ sec. post 4x4 ins. x 4 ft. long, 20" in ground, for ¼
sec. cor., from which

A Madrona 20" dia., bears S.4°W., 56 lks.

A Fir 4 ft. dia., bears N.28°W., 50 lks. dist.

BLM Resurvey - John Jelley, Lynn Roseberry, Floyd Brooks,
Under Group #s 320 and 614, - Surveyed June 1966 through May
1968. (DCSO records Vol. 35 Page(s) 14379-80)

The ¼ sec. cor. of secs. 5 and 8, determined at record
bearing and distance from the remaining original bearing
tree:

A burned Fir snag, 52" dia., bears N.28°W., 50 lks. dist.,
with illegible scribe marks visible on opened blaze.

At the Corner point

Set an iron post, 28 ins. long, 2½ ins. dia., 24 ins. in the
ground, with brass cap mkd: T 31 S R 5 W

¼ $\frac{S\ 5}{S\ 8}$
1966

from which new bearing trees:

A Madrone 7" dia., bears N.16°W., 77 lks. dist., mkd. ¼ S5
BT.

A Live Oak 5" dia., bears S.18½°E., 43½ lks. dist. mkd. ¼
S8 BT.

Ron Quimby - For: Cow Creek Indians 6/2016 - M171-12 A&B

Found - 1966 USBLM Brass cap

10" Madrone, N.16°W., 50.8' with no scar.

6" Oak N.18½°E., 28.7' with visible scribe.

New - 8" D.Fir S.44°W., 13.3' scribed "¼ S8 BT"

12" Pine N.61°W., 26.3' scribed "¼ S5 BT"