

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7924-25)

-----  
Set a Maple post, 4 ft. long, 4" square, 20" in ground for the cor. to secs. 20, 21, 28 and 29, marked T31S R5W S21 on the NE. face; S28 on the SE. face; S29 on the SW. face; and S20 on the NW face. Also two notches on the South and four notches on the East angles of the same, from which  
A Laurel 10" dia., bears N.25°E., 39 lks. marked T31S R5W S21 BT.  
A Laurel 14" dia., bears S.60°E., 28 lks. marked T31S R5W S28 BT.  
A Laurel 12" dia., bears S.41°W., 10 lks. marked T31S R5W S29 BT.  
A Maple 12" dia., bears N.34°W., 43 lks. marked T31S R5W S20 BT.

Survey by T.R. Eslinger, L.S. #268 - For: The California-Oregon Pacific Power Co. - Nov. 20, 1950 - C.S. File 40/280

-----  
All BTs found except Laurel, N.25°E., 29 lks. (down and rotted).  
Set 1½" Pipe flush with ground.  
Set 1½" x 40" Iron pin driven into ground with 10" exposed.  
Pin and pipe are side by side. (Old cedar post remains)

Survey by Victor S. King - For: Bate Lumber Co. - Oct. 30, 1959 - C.S. File 51/56-1

-----  
Found - 1¼" Iron rod.  
1 Orig. BT with scribing 14" Laurel S.60°E., 18.5'  
Set the following new bearing trees:  
12" Yew N.44°E., 43.7 ft. scribed S21 T31S R5W BT.  
16" Yew S.41½°W., 62.7 ft. scribed S29 T31S R5W BT  
Rescribed original BT, S28 T31S R5W BT.

Corner Fd. OK, by John Powell, DCSO, May 1966

BLM resurvey by James Jelley and Wayne Rogers under Group #1101 - Surveyed Sept. 1982\May 1983 (DCSO records Vol. 45 Page(s) 17488)

-----  
The Sec. Cor. perpetuated and recorded by Arthur Boyer in 1938, (Note: Boyer information erroneously received from DCSO-corner referred to was perpetuated by Eslinger in 1950 - V.L.) further perpetuated and recorded by King in 1959, (Cont. Next Page)

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

monumented with an iron rod, 1¼" dia., firmly set, projecting 4" above ground, from which the remains of the original bearing trees:

A Madrone 24" dia., bears S.60°E., 28 lks. dist., rescribed by King, with scribe marks T31S R5W BT visible on partially healed blaze.

A Maple root crown, size indeterminate, bears N.34°W., 43 lks. dist., no marks visible.

and bearing trees mkd. by King

A Yew 16" dia., bears N.43½°E., 65½ lks. dist., with scribe marks S21 T31S R5W BT visible on open blaze.

A Yew 20" dia., bears S.42°W., 95 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

At the corner point

Set an alum. post, 28 ins. long, 2½ ins. dia., 27 ins. in the ground directly over the iron rod, with alum. cap mkd:

T 31 S R 5 W  
S 20 | S 21  
S 29 | S 28  
1982

from which a new bearing tree

A Fir 8" dia., bears N.28½°W., 25 lks. dist., mkd. T31S R5W S20 BT.

Cor. Fd. OK, by Bruce Shaner, April 1993, C.S. File 63/149-12 and M 116-64

Fd. as per record 12/2018 by D. Edwards M175-11

Ron Quimby - 3/2020 - C.S. File 65/104-64

Found as per record

Set alum post S.43°W., 6.0 ft.

Set alum post in stump of 18" Fir stump old BT N.28½°W., 16.5 ft.