

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7926)

Set a basalt stone, 20x12x6 ins., 12" in ground for the 1/4 sec. cor., marked 1/4 on the W. face, from which
A Live Oak 15" dia., bears S.38°W., 44 lks. mkd. 1/4 S BT.
A Fir 12" dia., bears S.15°E., 29 lks. mkd. 1/4 S BT.

BLM resurvey by James Jelley and Wayne Rogers under Group #1101, surveyed, Sept. 1982/May 1983 (DCSO records Vol. 45 Page(s) 17488-89)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an alum. post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with alum. cap mkd: T 31 S R 5 W

S 20 | S 21
1982

from which
A Fir 8" dia., bears N.67°E., 73 lks., mkd. 1/4 S21 BT.
A Fir 5" dia., bears S.48 1/2°W., 5 1/2 lks., mkd. 1/4 S20 BT.

Ron Quimby - Crew: R. Heichel & J. Ogden - 2/2020 - C.S. File 65/104-47

Found - BLM brass cap (properly mkd)
16" Fir N.67°E., 48.2 ft. (burnt)
12" Fir S.48 1/2°W., 3.6 ft. (burnt)
New - PK in rock N.60°E., 7.4 ft.
5/8"x30" I.Rod N.36°W., 3.4 ft.
5/8"x30" I.Rod S.78°W., 4.5 ft.
5/8"x30" I.Rod S.85°E., 5.5 ft.
All rods have yellow plastic cap stamped "ie engineering". 5' Alum. post alongside.
Note - Area badly burnt 2019
Compass decl. 15 1/2°E.