

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for secs. 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7926)

Set a Fir post, 4 ft. long, 4" square, 20" in ground for the cor. to secs.16, 17, 20 and 21, marked T31SR5W S16 on the NE. face, S21 on the SE. face, S20 on the SW. face, and S17 on NW. face. Also, three notches on the South and four notches on the East angles of the same, from which
A Fir 8" dia., bears N.64°E., 43 lks. mkd. T31S R5W S16 BT
A Fir 6" dia., bears S.56°E., 30 lks. mkd. T31S R5W S21 BT
A Fir 8" dia., bears S.20°W., 14 lks. mkd. T31S R5W S20 BT
A Fir 5" dia., bears N.62°W., 24 lks. mkd. T31S R5W S17 BT

Survey by Victor S. King - For: Bate Lumber Co. - Oct. 30, 1959 - C.S. File 51/56-5

Found - This corner falls in an old burn. Corner was set on the intersection of the original blazes, then when the corner was occupied, I turned off the correct bearings and distances to 4 old Fir stumps that fit the bearings and distances to the 4 orig. BTs perfectly. No scribing remained on any of the old bearing trees.
Set 3" Fir post, from which I set the following new BTs:
6" Fir N.56°E., 10.4 ft. scribed S16 T31S R5W BT.
3" Fir N.55°W., 18.3 ft. scribed S17 T31S R5W BT.
22" Fir S.46°W., 20.8 ft. scribed S20 T31S R5W BT
6" Fir S.83°E., 39.6 ft. scribed S21 T31S R5W BT.

Douglas Co. Surveyors Office - John Powell, Frank Jones and Joe Brady - My 1966 - C.S. File 54/25-9

Found - Sq. stake at sec. cor., scribed "S44" legible.
3" D.Fir now 6" N.55°W., 18.2 ft. shows good scar.
6" D.Fir now 9" N.56°E., 10.4 ft scribe visible "16"
6" D.Fir now 9" S.83°E., 39.6 ft. shows good scar.
22" D.Fir S.46°W., 20.8 ft. scribe visible but pitched over too good to read.
Set Brass cap at sec. cor. mkd: County Surveyors Office
T 31 S R 5 W
S 17 | S 16
S 20 | S 21
1966

All bearing trees in good condition.

Cor. Fd. OK, BLM survey by Jelley & Rogers, 1982/83 (DCSO records. Vol. 45 Pages 17489-90

-----Cont.

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for secs. 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ron Quimby - Crew: N. Fromdahl, R Heichel & J. Ogden - 9/2019
- C.S. File 65/104-11

Found - 1966 DCS0 brass cap (properly mkd)
 20" D.Fir N.55°W., 18.2 ft. good scar.
 24" D.Fir N.56°E., 10.4 ft. good scar.
 18" D.Fir S.83°E., 39.6 ft. good scar.
New - 12" D.Fir S.68°W., 14.6 ft. scribed T31S R5W S20 BT
Note - Area badly burnt 2019
 Compass decl. 15½°E.