

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7927)

Set a Fir post, 3 ft. long, 3" square, 18" in ground for the 1/4 sec. cor., marked 1/4 S on the W. face, from which
A Laurel 4" dia., bears N.40°E., 4 lks. mkd. 1/4 S BT.
A Fir 12" dia., bears S.75°W., 41 lks. mkd. 1/4 S BT.

Survey by Victor S. King - For: Bate Lumber Co. - Oct. 30, 1959 - C.S. File 51/56-4

Found - Original BT with scribing, 30" Fir S.75°W., 41 lks.
Set 3" Fir Post.
New BT - 34" Fir S.78°E., 34.0 ft. scribed S16 T31S R5W BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones and Joe Brady - May 1966 - C.S. File 54/25-18

Found - Fir post at corner.
Orig. 30" Fir, now 40", S.75°W., 27.1 ft. opened for old scribe marks. Had been opened but could not see any marks.
34" D.Fir now 36", S.78°E., 34.0 ft. shows good face
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 5 W
1/4 S 17 | S 16
1966

Reblazed and rescribed:
40" D.Fir S.75°W., 27.1 ft. scribed "1/4 S17 CS BT"
(This tree is Double Fir)
Corner lies in bottom of small ravine.

Survey by Mark Smalley - For: Roseburg Resources - Sept. 1991 - C.S. File 63/129

Found - DCSO brass cap dated 1966.
34" D.Fir now 42" bears S.78°E., 34 ft.
Orig. 40" D.Fir now a stump.
Set 5/8" x 54" iron rod and alum. cap reference monument, bears S.45°W., 10.0 ft.
Corner lies 250 ft. above Road 31-5-17.2, in a recent clearcut.

Ron Quimby - Crew: N. Fromdahl & L. Heddens - 2/2020 - C.S. File 65/104-56

Found - DCSO Brass cap (properly mkd)
42" Burnt stump S.78°E., 34.0 ft. Cont. next pg

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

| | | | |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

| | |
|--------|--|
| New - | 5/8" I.Rod with alum cap S.45°W., 10.0 ft. |
| | 5/8"x30" I.Rod N.45°E., 5.0 ft. |
| | 5/8"x30" I.Rod S.45°E., 7.0 ft. |
| | 5/8"x30" I.Rod N.45°W., 5.0 ft. |
| | Iron rods have yellow plastic cap stamped "ie engineering". 5' Alum. post alongside. |
| Note - | Area badly burnt 2019 |
| | Compass decl. 15½°E. |