

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7929-30)

-----  
Set a stone 15x10x6 ins., 10" in ground, marked  $\frac{1}{4}$  on W. face, for the  $\frac{1}{4}$  sec. cor., from which

A Fir 6" dia., bears N.52°E., 21 lks. dist. mkd.  $\frac{1}{4}$  S BT.

A Fir 12" dia., bears S.55°W., 24 lks. dist., mkd.  $\frac{1}{4}$  S BT

BLM Corrective Resurvey - John Jelley, Lynn Roseberry, Floyd Brooks, Under Group #s 320 and 614, - Surveyed June 1966 through May 1968. (DCSO records Vol. 35 Page(s) 14368-69)

-----  
Point for the  $\frac{1}{4}$  sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. dia., 24 ins. in the ground, with brass cap mkd:

T 31 S R 5 W

$\frac{1}{4}$

S 8 S 9

1966

from which

A Fir 14" dia., bears S.67°E., 17 lks. dist., mkd.  $\frac{1}{4}$  S9 BT

A Fir 25" dia., bears N.47°W., 51 $\frac{1}{2}$  lks. dist. mkd.  $\frac{1}{4}$  S8 BT