

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.P.Wright, under Contract #261, dated May 16, 1878 (DCSO records Vol. 19 Page(s) 7890 and 7888-89)

(Page 7888-89)

At 9.00 chs. N. of post cor. to secs. 4, 5, 8 and 9, Set post 4 x 4 ins. x 3½ ft. long, 20" in ground, for WITNESS CORNER to secs. 4 and 5, from which

A Fir 10" dia., bears N.24°W., 15 lks.

A Fir 10" dia., bears S.13°E., 22 lks.

This post sets on steep hill side, sloping NE. The Mt. S. and W. very steep.

(Page 7890)

At 23.07 chs. East of cor. to secs. 4, 5, 8 and 9, Set post 4 x 5 ins. by 3 ¾" ft. long in mound of rock for WITNESS CORNER, from which

A dead Fir 40" dia., bears N.3°W., 138 lks.

A green Fir 10" dia., bears N.50°W., 110 lks.

GLO survey by W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7929)

At a point, 5.80 chs. East of a point due South of the established witness cor. to secs. 4 and 5, at which point, I establish a witness cor. to secs. 8 and 9 by setting a Fir post, 4" square, 20" in ground, marked T31S R5W on NE. face, S9 on SE. face, S8 on SW. face and W.C. on NW. face, also five notches on the S. and 3 notches on E. angles of same. Made stone mound, 3 ft. high, 4 ft. at base. Pits impracticable, unable to reach Witness corner between secs. 3 and 4 to ascertain the distance from this established witness corner.

BLM Corrective Resurvey - John Jelley, Lynn Roseberry, Floyd Brooks, Under Group #s 320 and 614, - Surveyed June 1966 through May 1968. (DCSO records Vol. 35 Page(s) 14369)

At 80.20 chs. record distance for witness cor. for cor. secs. 4, 5, 8 and 9; there is no remaining evidence of the original corner.

At 83.14 chs., point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original witness corners.

Set an iron post, 28 ins. long, 2½ ins. dia., 22 ins. in the ground, with brass cap mkd:

T 31 S R 5 W

S 5 | S 4

S 8 | S 9

1966 (Cont. Next Page)

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

from which

- A White Fir 12" dia., bears N.83°E., 87½ lks. dist., mkd. T31S R5W S4 BT.
- A Cedar 17" dia., bears S.76½°E., 295 lks. dist., mkd. T31S R5W S9 BT.
- A Fir 10" dia., bears S.46°W., 26 lks. dist., mkd. T31S R5W S8 BT.
- A Fir 25" dia., bears N.61°W., 212 lks. dist., mkd. T31S R5W S5 BT.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 10/19/2006 - C.S. File 67/14-39

-
- Found - 3" dia., BLM BC on 2½" O.D. IP projects 3" above ground in small mound of stones.
12" now 23" dia., W.Fir healed single blaze, bears N.83°E., 57.8 ft. (agrees w/rec.)
10" now 13" dia., x 1' tall rotten fir stump part of low healed blaze visible bears S.46°W., 17.2 ft. (agrees w/rec.)
17" cedar not found, falls in road/landing
25" now 30" dia., x 2' tall stump, evidence of healed blaze visible bears N.59°W., 141.5 ft. (rec. N.61°W., 139.9 ft.)
- New - 11" dia., D.Fir, double blazed & scribed "T31S R5W S9 CS BT" bears S.17°E., 19.5 ft.
8" dia., D.Fir, double blazed & scribed "T31S R5W S8 CS BT" bears S.55¾°W., 15.7 ft.
7" dia., D.Fir double blazed & scribed "T31S R5W S4 CS BT" bears N.71°W., 22.9 ft.
- Note - Corner position falls on ridge top approx. 30 ft. North of logging road.
Compass decl. 16½°E.

Fd. BC & 5 BTs by R. Quimby, 6/2016 - M171-12 A&B