

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7925)

Set a basalt stone 15x14x5 ins., 10" in ground for the ¼ sec. cor., marked ¼ on N. face, from which

A Fir 34" dia., bears S.15°E., 22 lks. dist. mkd. ¼ S BT.

A Laurel 7" dia., bears N.68°E., 22 lks. dist., mkd. ¼ S BT.

Survey by Bruce Shaner L.S. #430 - For: Richard McKenzie - April 1993 - M 116-64 and C.S. File 63/149

Set 2½" Brass cap on 1" x 30" galv. iron pipe marked "SHANER ENGR. 1/4 S 21, 28 RLS 430 1993"

New Accessories:

8" D.Fir, N.2°W., 4.7 ft. scribed ¼ S BT.

10" D.Fir, N.43°E., 18.2 ft. scribed ¼ S BT.

6" D.Fir, S.15°E., 8.8 ft. scribed ¼ S BT.

8" D.Fir, S.43°W., 13.4 ft. scribed ¼ S BT.

Set steel fence post on road at 600 ft. West of ¼ Sec. cor.

Fd. Ok 2/2020 - R. Quimby - C.S. File 65/104-63