

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Sec. 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Jelley, Roseberry, and Brooks, under Group #'s 320 and 614 - Surveyed June 1966/May 1968 (DCSO records, Vol. 35 Page 14363)

Point for the ¼ sec. cor. of sec. 4 only, on the N. bdy. of the Tp., at midpoint in departure on the N. bdy. of sec. 4. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

¼ S 4
T 31 S R 5 W
1967

from which

A Fir 22" dia., bears S.49½°E., 149½ lks. dist., mkd. ¼ S4 BT.

A Fir 15" dia., bears S.26 3/4°W., 60½ lks. dist., mkd. ¼ S4 BT.

Found OK, Nov. 1993 by R.Brown - M 119-12.
Found OK, March 1995 by R.Brown - M 121-80
Fd. BC by R. Brown, 10/2013 - M166-4

Ron Quimby - For: C & D Lumber Co. - Nov. 2014 - M166-22

Found - Brass cap per 1966-1968 BLM resurvey
36" Fir S.49°E., 98.7' healed face
32" Fir S.26°W., 39.9' healed face
New - 10" Madrone N.12°W., 17.4' scribed "¼ BT"