

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7914)

Set a stone 13x12x7 ins., 8" in ground, for the cor. to secs. 27, 28, 33 and 34, marked with 3 notches on E. and 1 notch on S. edges, from which

- A Maple 7" dia., bears N.44°E., 14 lks. dist. mkd. T31S R5W S27 BT.
- A Cedar 30" dia., bears S.78°E., 75 lks. dist. mkd. T31S R5W S34 BT.
- A Laurel 8" dia., bears S.12°W., 58 lks. dist., mkd. T31S R5W S33 BT.
- A Fir 36" dia., bears N.36°W., 56 lks. dist., mkd. T31S R5W S28 BT.

GLO resurvey by Hans W. Thielsen, under Group #320, Surveyed, Oct./Nov. 1955 - (DCSO records Vol. 28 Page(s) 11788-89)

The Sec. Cor. determined at record bearing and distance from the remaining original bearing trees:

- A Cedar 48" dia., bears S.78°E., 75 lks. dist., marked T31S R5W S34 BT on bark.
- A Fir 50" dia., bears N.36°W., 56 lks. dist., with marks S 28 BT remaining on bark.

At corner point

Set an iron post, 36 ins. long, 2 ins. dia., 30 ins. in the ground, with brass cap mkd:

T 31	S R 5 W
S 28	S 27
S 33	S 34
1955	

from which new bearing trees

- A Red Fir 25" dia., bears N.76¼°E., 48 lks. dist., marked T31S R5W S27 BT.
- A Hemlock 15" dia., bears S.24°E., 84 lks. dist., marked T31S R5W S34 BT.
- A Red Fir 15" dia., bears S.35°W., 71 lks. dist., marked T31S R5W S33 BT.
- A Sugar Pine 20" dia., bears N.26°W., 62 lks. dist., marked T31S R5W S28 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones and Joe Brady - May 1966 - C.S. File 54/25-22

Found - 1955 GLO brass cap at corner.
25" R.Fir now 26" N.76°E., 31.7 ft. pitched over, scribing visible.
15" R.Fir now 17" S.35°W., 46.9 ft. shows good scar.
(Cont. Next Page)

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

15" Hemlock, now blown down, S.24°E., 55.1 ft.
20" Pine, now blown down, N.26°W., 40.9 ft.
New BTs -5" Live Oak N.87°W., 19.0 ft. scribed S28 CSBT.
8" Maple S.12°E., 31.0 ft. scribed T31S R5W S34 CSBT
This corner lies in deep draw with creek South, 50.0 ft.

Corner Fd. and tied in BLM survey by Jelley, Roseberry and Brooks, 1966-68 - (DCSO records, Vol. 35 Page 14389)

David Edwards - For: Roseburg Resources - Dec. 2018 - M175-11

Found - Brass cap
40" tall 26" dia., capped fir stump bears N.76°E.,
31.7'
13" dia. Maple bears S.12°E., 31.0'
24" dia., fir w/healed scar bears S.35°W., 46.9'
Set - A six ft. steel post 2' south

Ron Quimby - Crew: N. Fromdahl & L. Heddens - 3/2020 - C.S.
File 65/106-4

Found - GLO brass cap (properly mkd)
26" capped fir stump N.76°E., 31.7 ft.
13" maple S.12°E., 31.0 ft. (charred)
24" Fir S.35°W., 46.9 ft. (charred)
Steel post 2 south.
New - 12" Fir N.74°W., 43.3 ft. scribed T31S R5W S28 BT.
18" Fir N.12°E., 26.0 ft. scribed T31S R5W S27 BT.
Alum. post 2.0 west.
Note - Area badly burnt 2019
Compass decl. 15½°E.