

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 page 7916)

Set Laurel post, 4 ft. long, 4" square, 22 in ground, for the cor. to secs.21, 22, 27 and 28, marked T31S R5W S22 on NE., S.27 on SE., S28 on SW. and S21 on NW. faces, with 2 notches on the South and 3 notches on the East edges, from which
A Laurel 12" dia., bears N.55°E., 26 lks. marked T31S R5W S22 BT.
A Fir 15" dia., bears S.30°E., 15 lks. dist. marked T31S R5W S27 bT.
A Fir 40" dia., bears S.87°W., 62 lks. dist., marked T31S R5W S28 BT.
A Laurel 15" dia., bears N.20°W., 13 lks. dist., marked T31S R5W S21 BT.

Survey by Victor S. King - For: Bate Lumber Co. of Merlin, OR - Oct. 30, 1959 - C.S. File 51/56-6

Found - 1 Orig. BT with scribing, S.30°E., 9.9 ft.
Set 4" Fir post from which I set the following new bearing trees:
16" Fir N.66°E., 29.0 ft. scribed S22 T31S R5W BT.
30" Fir N.32°W., 54.3 ft. scribed S21 T31S R5W BT.
14" W.Fir S.51°W., 19.5 ft. scribed S28 T31S R5W BT.
32" Fir O.B.T., S.30°E., 9.9 ft. rescribed S27 T31S R5W BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones and Joe Brady - May 1966 - C.S. File 54/25-25

Found - Scribed stake mkd. "RS 442".
16" D.Fir N.66°E., 29.0 ft. shows good pitched over scribe marks.
36" D.Fir N.32°W., 54.3 ft. shows good face.
14" W.Fir S.51°W., 19.5 ft. scribe visible "T31S R5W BT".
Orig. 32" D.Fir S.30°E., 9.9 ft. shows good face.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 5 W
S 21 | S 22
S 28 | S 27
1966

All bearing trees in good condition.

Cor. Fd.OK by BLM resurvey by Berry and Akin, 1972-73, DCSO records, Vol. 38 Page 15684

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Cor. Fd. OK, by Bruce Shaner, April 1993, C.S. File 63/149-12 and M 116-64

Ron Quimby - Crew: N. Fromdahl & J. Ogden - 9/2019 - C.S. File 65/104-9

Found - 1966 DCS0 brass cap (properly mkd)
18" burnt D.Fir stump N.66°E., 29.0 ft.
36" burnt D.Fir stump N.32°W., 54.3 ft.
24" W.Fir S.51°W., 19.5 ft. good scar.
44" D.fir S.30°E., 9.9 ft. good scar.
New - 7" D.Fir N.46°W., 23.6 ft. scribed: T31S R5W S21 BT.
5/8"x30" I.Rod N.48°E., 12.9 ft. with yellow cap "ie
engineering"
Note - Area burnt badly 2019
Compass decl. 15½°E.