

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7917)

-----  
Set a Fir post, 3 ft. long, 3" square, 18" in ground, for 1/4 sec. cor., marked 1/4 on West face, from which  
A Cedar 28" dia., bears N.25°E., 19 lks. mkd. 1/4 S BT.  
A Cedar 26" dia., bears S.35°W., 34 lks. mkd. 1/4 S BT.

Survey by Victor S. King, For: Bate Lumber Co. - Oct. 30, 1959 - C.S. File 51/56-8

-----  
Found - 2" square post and 2 original bearing trees with scribing.  
Rescribed original bearing trees in bark:  
44" Cedar N.25°E., 12.5 ft. rescribed 1/4 S22 BT.  
32" Cedar S.35°W., 22.4 ft. rescribed 1/4 S21 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones and Joe Brady - May 1966 - C.S. File 54/25-24

-----  
Found - Fir post at 1/4 corner.  
44" Cedar N.25°E., 12.5 ft. bark scribed 1/4 S22 BT.  
32" Cedar S.35°W., 22.4 ft. bark scribed 1/4 S21 BT.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 5 W  
1/4 S21 | S22  
1966  
New BTs -12" Pine S.71°E., 34.0 ft. scribed 1/4 S22 CS BT.  
15" D.Fir S.73°W., 19.2 ft. scribed 1/4 S21 CS BT.  
This corner is about 360.0 ft. South of power line.

BLM resurvey by James Jelley and Wayne Rogers - under Group #1101 - Surveyed, Sept. 1982/May 1983 - (DCSO records Vol. 45 Page(s) 17485-86)

-----  
The 1/4 sec. cor., perpetuated and recorded by King in 1959 and further perpetuated and recorded by Powell in 1966, monumented with an iron post, 1 1/4" dia., firmly set, projecting 10" above ground, with properly mkd. brass cap. from which the original bearing trees  
A Cedar 46" dia., bears N.31°E., 23 lks. dist., rescribed by King, with scribe marks 1/4 S22 BT visible on bark blaze. (Rec. N.25°E., 19 lks.)  
A Cedar 37" dia., bears S.24°W., 34 lks. dist., with scribe marks 1/4 S visible on bark blaze, rescribed by King, with scribe marks 1/4 S BT visible on bark blaze. (Rec. S.35°W.)

(Cont. Next Page)

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of bearing trees mkd. by Powell  
A Pine 15" dia., bears S.71°E., 51 lks. dist., with healed blaze.  
A Fir snag 15" dia., bears S.73°E., 28 lks. dist., with fragmentary scribe marks visible on partially healed blaze.  
and a new bearing tree  
A Fir 9" dia., bears N.59¼°W., 55 lks. dist., mkd. ¼ S21 BT.

Ron Quimby - Crew: R. Heichel & J. Ogden - 1/2020 - C.S. File 65/104-40

-----

Found - DCS0 Brass cap (properly marked)  
50" Cedar N.31°E., 15.2 ft. bark scribed.  
23" Pine S.71°E., 33.7 ft. good scar.  
11" Fir N.59¼°W., 36.3 ft. good scar.

New - 5/8" I.Rod S.50°W., 6.2 ft. with yellow plastic cap stamped "ie engineering"

Note - Area badly burnt 2019  
Compass decl. 15½°E.