

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7919)

-----  
Set a Laurel post, 4 ft. long, 4" square, 20" in ground, marked T31SR5W S10 on NE. face, S15 on SE. face, S16 on SW. face, S9 on NW. face, also four notches on the South and three notches on the East angles of same for the corner to sections 9, 10, 15 and 16, from which

- A Fir 40" dia., bears N.15°E., 62 lks. dist., marked T31S R5W S10 BT.
- A Laurel 5" dia., bears S.70°E., 7 lks. dist., marked T31S R5W S15 BT.
- A Laurel 8" dia., bears S.65°W., 29 lks. dist. marked T31S R5W S16 BT.
- A Chinquapin 12" dia., bears N.35°W., 22 lks. dist. marked T31S R5W S9 BT.

Richard L. Templin, Jr. - Sept. 3, 1957 - C.S. 42/303

-----  
Found - 38" Fir N.15°E., 62 lks. with faint axe marks on bark which was burned. No scribing visible. Knife scribe this tree in bark on root collar "BT" and set aluminum poster tag 4 x 5 5/8" on SW side of tree, 5 ft. above ground.  
6" dead Madrone, S.70°E., 7 lks. with partially healed face and portion of original scribed face with scribing.  
Rotted stub of 12" Chinquapin, N.35°W., 22 lks. projecting 10" above ground.  
Madrone in SW quadrant, not found.

Survey by Victor S. King - For: Bate Lumber Co. - Aug. 11, 1960 - C.S. File 51/56-10

-----  
Found - Orig. BT, 52" Fir, no scribing, N.15°E., 62 lks.  
Orig. BT, 8" Laurel with scribing very faintly visible; blaze for scribing plainly visible.  
This BT is dead and down, S.70°E., 7 lks.  
Orig. line blazes to South and West.

Set 1½" Iron pipe 42" long, 30" in ground, from which the following new bearing trees:

- 10" Chinquapin, N.50½°W., 11.3 ft. scribed T31S R5W S9 BT
- 12" Chinquapin, S.15½°W., 31.7 ft. scribed T31S R5W S16BT
- 48" Fir S.69°E., 37.0 ft. scribed T31S R5W S15 BT.
- Rescribed Orig. BT, in bark, 52" Fir N.15°E., 62 lks.

cont.

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15685)

-----  
The Sec. Cor., perpetuated and recorded by Victor King in 1960, monumented with an iron pipe, 1" dia., firmly set, protruding 12" above ground, from which the remains of the original bearing trees:

A Fir 52" dia., bears N.12°E., 66 lks. dist., with scribe marks T31S R5W S10 BT visible on bark blaze. (Rec. N.15°E., 62 lks.)

A root hole, bears S.70°E., 7 lks. dist., with a down madrone alongside, 6" dia., with scribe marks BT visible on opened blaze.

and bearing trees mkd. by King:

A Fir 40" dia., bears S.70½°E., 57 lks. dist., with healed blaze.

A Chinquapin 22" dia., bears S.15°W., 48 lks. dist., with scribe marks T31S R5W S16 BT visible on open blaze.

A Chinquapin 10" dia., bears N.51°W., 17 lks. dist., with scribe marks T31S R5W S9 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. dia., 22 ins. in the ground, with brass cap mkd:

T 31 S R 5 W  
S 9 | S 10  
S 16 | S 15  
1973

Deposit iron pipe alongside iron post.

Ron Quimby - Crew: R. Heichel & J. Ogden - 1/2020 - C.S. File 65/104-42

-----  
Found - BLM Brass cap (properly marked)  
58" Fir N.12°E., 43.6 ft. bark scribed.  
50" Fir S.70½°E., 37.6 ft. good scar.

New - 5/8" I.Rod S.30°W., 8.3 ft.  
5/8" I.Rod N.78°W., 5.6 ft.  
Both have yellow plastic cap stamped "ie engineering". Alum. post alongside.

Note - Area badly burnt 2019  
Compass decl. 15½°E.