

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7921)

-----  
Set a stone 12x8x8 ins., 10" in ground, marked ¼ on the West side for the ¼ sec. cor. and from which  
A Laurel 12" dia., bears N.43°E., 10 lks. mkd. ¼ S BT.  
A Fir 46" dia., bears N.35°W., 41 lks. mkd. ¼ S BT.

Arthur R. Evans, R.E. #2741 - Wit: Glen Murdock - For: Umpqua Plywood Corp. - Feb. 10, 1955 - C.S. File 41/356-2

-----  
Found - Orig. stone and 50" Fir, N.35°W., 41 lks., checks for bearing and distance.  
Blazed and scribed new trees:  
7" Madrone N.37°E., 13.7 ft. to center of tree at scribe marks, tree leans to North, mkd. ¼ S10 BT.  
7" Madrone South 8.8 ft. to center of tree at scribe marks, mkd. ¼ S9 BT. Copper tag, R.E. 1741.

Survey by Victor S. King - For: Bate Lumber Co. - Oct. 30, 1959 - C.S. File 51/56-2

-----  
Found - Two Madrona BTs set by Evans and 4" Fir post, both since destroyed by logging.  
Set - 1 1/8" Iron rod, 36" long, 14" in ground in a small mound of stones.  
New BTs -8" Fir S.82°W., 40.3 ft. scribed ¼ S9 T31S R5W BT.  
48" Cedar S.53°E., 78.0 ft scribed ¼ S10 T31S R5W BT

Douglas Co. Surveyors Office - John Powell, Frank Jones and Joe Brady - May/June 966 - C.S. File 54/25-26

-----  
Found - 1 1/8" Iron pipe.  
8" Fir broken off, S.82°W., 40.3 ft. scribe visible.  
48" Cedar now stump, S.53°E., 78.0 ft. scribe visible "S10 T31S R5W BT."  
New BTs -6" D.Fir scribed ¼ S9 CS BT, N.83°W., 21.6 ft.  
18" Cedar S.24½°E., 92.9 ft. scribed ¼ S10 CS BT.

Ron Quimby - Crew: R. Heichel & J. Ogden - 1/2020 - C.S. File 65/104-43

-----  
Found - 1 1/8" IP  
48" cedar stump S.53°E., 78.0 ft. vis. scribe.  
New - 5/8" I.Rod S.30°W., 5.9 ft.  
5/8" I.Rod N.74°W., 5.6 ft.  
5/8" I.Rod S.52°E., 5.1 ft.  
5/8" I.Rod N.32°E., 5.2 ft. Continued next page

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Note - All rods have yellow plastic cap stamped "ie  
engineering". 5' Alum. post alongside.  
Area badly burnt 2019  
Compass decl. 15½°E.