

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. P. Wright under Contract #281 dated May 16, 1878 (DCSO records Vol. 19 Page(s) 7890)

Set post 5x5 ins. by 4½ ft. long in mound of rock on top of ridge to secs. 3, 4, 9 and 10.
No witness trees. This post is in an open place.

Douglas Co. Surveyors Office - Ben B. Irving, Surveyor - Wit: R.L. Irving; N.E. Richardson - Nov. 14-22, 1930 - C.S. File 16/45; C.S. File 37/25 and "old" Corner book, page 162

24" Fir S.70°W., 37.5 ft. S9 T31S R5W CS BT.
18" Fir N.31°W., 39.0 ft. S4 T31S R5W CS BT.
12" Fir N.10°E., 66.5 ft. S3 T31S R5W CS BT.
Original corner as described original notes.

Survey by John H. Markham, Jr. - For: Canyon Logging - Wit: D.E. Brown - Sept. 13, 1957 - C.S. File 42/312

Section corner as determined by old BTs.
Found - At cor. point, found 3 ft. pile of stones with scribed 3" x 3" post in center.
I Set a 1/2" x 20" Iron rod at corner.
Found two bark scribed BTs which I tagged.
Corner lies on top of high side ridge, on West edge of large burn. Airplane beacon bears N.8°12'W., 1245.0 ft. on 20°00 Var.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones and Joe Brady - April/May 1966 - C.S. File 54/25-3

Found - Mound of stone and old scribe stake.
Also ½" Iron rod.
Two BTs found in 1957, but no record of them.
36" Fir S.71°W., 28.5 ft. bark scribed.
26" Fir N.29°W., 38.5 ft. bark scribed.
New BTs -6" D.Fir N.21°E., 48.0 ft. scribed T31S R5W S3 CS BT
4" Live Oak S.69°E., 32.0 ft. scribed T31S R5W S10 CS BT.
Reblazed and rescribed
36" D.Fir S.71°W., 28.5 ft. mkd. T31S R5W S9 CS BT.
26" D.Fir N.29°W., 38.5 ft. mkd. T31S R5W S4 CS BT.

BLM Corrective Resurvey - John Jelley, Lynn Roseberry, Floyd Brooks, Under Group #s 320 and 614, - Surveyed June 1966 through May 1968. (DCSO records Vol. 35 Page(s) 14366-67)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

The Sec. cor., monumented with the original mound of stone, 3 ft. base, 1 ft. high, perpetuated and recorded by Irving in 1930, again perpetuated and recorded by Markham in 1957, monumented with an iron rod, 20" long, ½" dia., firmly set 10" in the ground and in center of original mound of stone, from which bearing trees mkd. by Irving in 1930:

A Fir 34" dia., bears S.72°W., 58 lks. dist. with illegible scribe marks visible on bark. Remarkd T31S R5W S9 BT on double blaze by County Surveyor in 1966.

A Fir 25" dia., bears N.29°W., 59 lks. dist., with illegible scribe marks visible on bark. Remarkd T31S R5W S4 CS BT on double blaze by the County Surveyor in 1966.

and bearing trees mkd. by the County in 1966

A Fir 6" dia., bears N.20°E., 72 lks. dist., with scribe marks T31S R5W S3 CS BT visible on open double blaze.

A Live Oak 6" dia., bears S.68°E., 44 lks. dist., with scribe marks T31S R5W S10 CS BT visible on open double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. dia., 21 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

T 31 S R 5 W				
<table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 10</td> </tr> </table>	S 4	S 3	S 9	S 10
S 4	S 3			
S 9	S 10			
1966				

Deposit the iron rod alongside the iron post.

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch
 - Feb. 21, 2013 - C.S. File 67/38-21

Found - A 3⅛" dia., brass cap (properly mkd) on a 2½" O.D. iron pipe firmly and plumbly set protruding 2" from a rough mound of stone measuring approx. 30" in dia., and 1/2 ft. tall 1966 BLM corrective resurvey.

1957 monument not evident.

A 24" fir now a 39" dia., D.Fir with a fully healed double blaze; bears S.72°W., 37.5 ft. (bearing agrees with 1966 BLM record, dist agrees with 1957 rec.) 1930

An 18" fir now a 36" dia., D.Fir with a fully healed double blaze; bears N.28°W., 39.0 ft. (rec. N.31°W., 39.0 ft.) 1930

1957 tower reference not checked; there are now many towers on ridge top.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

A 6" D.Fir now a 14" dia., 16" tall rotted fir stump with a healed low blaze (blaze opened to show scribing "BT") 1966
 A 4" Live Oak now a rotted and broken 3" dia., .1 ft. tall oak stump with remnants of a partially healed blaze showing the scribing "BT"; bears S.66½°E., 29.6 ft. (rec. S.69°E., 32.0 ft.) Broken off 5" dia., trunk has a partially healed blaze showing the scribing " WS10CS" 1966
 New - A 6" dia., Live Oak scribed "X" "CSBT" on a double blaze; bears N.75½°E., 23.2 ft.
 A 7" dia., Live Oak scribed "X" "CS BT" on a double blaze; bears S.89½°E., 29.0 ft.
 Note - Monument is on more-or-less flat ground at top of high southerly running ridge. Ridge is near summit of, and on south flank of Canyon Mountain. Area has scattered firs and live oak with low dense brush.
 Compass decl. 15½°E.

Ron Quimby - Crew: R. Heichel & J. Ogden - 2/2020 - C.S. File 65/104-51

 Found - BLM brass cap (properly mkd)
 40" Fir S.72°W., 37.5 ft. (healed scar charred)
 36" Fir N.28°W., 39.0 ft. (healed scar charred)
 6" Live Oak N.75°E., 23.2 ft (faint scribes charred)
 7" Live Oak S.89°E., 29.0 ft (faint scribes charred)
 New - ⅝" I.Rod S.56°W., 4.2 ft.
 ⅝" I.Rod N.43°W., 4.2 ft.
 ⅝" I.Rod N.54°E., 10.9 ft.
 ⅝" I.Rod S.52°E., 5.1 ft.
 All rods have yellow plastic cap stamped "ie engineering". 5' Alum. post alongside.
 Note - Area badly burnt 2019
 Compass decl. 15½°E.