

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7920)

-----  
Set a stone, 12x12x8 ins., 9" in ground, marked ¼ on the N. side for the ¼ sec. cor., from which  
A Cedar 20" dia., bears S.45°W., 12 lks. dist. mkd ¼ S BT  
A Laurel 5" dia., bears N.44°E., 16 lks. dist. mkd ¼ S BT

Arthur R. Evans R.E. 2741 - Wit: Glen Murdock - For: Umpqua Plywood Corp. - Feb. 10, 1955 - C.S. File 41/356-1

-----  
Reset from old Cedar BT, 20" now 32" Cedar, S.45°W., 12 lks. Set 3" x 3" x 48" Fir stake for corner.  
Rescribe old Cedar BT, S.45°W., re-measure to center of tree on upper side, 9.9 ft. mkd. "¼ S - 10 - B.T."  
Blaze and scribe new BT:  
28" D.Fir S.16°E., 5.0 ft. dist. to center on lower side mkd. ¼ S - 15 - B.T. - copper tag - R.E. 2741.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones and Joe Brady - May/June 1966 - C.S. File 54/25-21

-----  
Found - Wooden stake at ¼ cor., distances to face of trees. Orig. 32" Cedar now 36", S.45°W., 7.9 ft. bark scribed "¼S"  
28" D.Fir now 32", S.16°E., 5.0 ft. pitched over, scribing legible.

Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 5 W  
¼  $\frac{S\ 10}{S\ 15}$   
1966

Reblazed and rescribed:  
36" Cedar S.45°W., 7.9 ft. scribed ¼ S15 CS BT.  
New BT - 16" Laurel N.19°E., 15.5 ft. scribed ¼ S10 CS BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15684)

-----  
Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. dia., 22 ins. in the ground, with brass cap mkd: T 31 S R 5 W

¼  $\frac{S\ 10}{S\ 15}$   
1973

(Cont. Next Page)

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. For Secs. 10 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

from which

A Fir 40" dia., bears S.42½°E., 11 lks. dist. mkd. ¼ S15  
BT.

A Fir 21" dia., bears N.11°W., 59½ lks. dist., mkd. ¼ S10  
BT.