

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 surveyed July 28, 1882 (DCSO rec. Vol. 19 Page 7904)

Set a Laurel post, 3 ft. long, 3" square, 18" in ground, marked $\frac{1}{4}$ S on the West side for the $\frac{1}{4}$ sec.cor., from which
A Laurel 14" dia., bears S.70°E., 20 lks. mkd. $\frac{1}{4}$ S BT.
A Laurel 7" dia., bears S.75°W., 18 lks. mkd. $\frac{1}{4}$ S BT.

GLO resurvey by Hans W. Thielsen, under Group #320, Surveyed, Oct./Nov. 1955 - (DCSO records Vol. 28 Page(s) 11787)

The $\frac{1}{4}$ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

At the corner point

Set an iron post, 36 ins. long, 1 in. dia., 30 ins. in the ground, with brass cap mkd:

$\frac{1}{4}$
S 34 | S 35
1955

from which

A Red Fir 22" dia., bears S.31°E., 62 lks. marked $\frac{1}{4}$ S35 BT

A Red Fir 17" dia. bears S.72°W., 37 lks., marked $\frac{1}{4}$ S34 BT

BLM Corrective Resurvey - John M. Jelley, Lynn M Roseberry, Floyd A Brooks, under Group #s 320 and 614 - Surveyed, June 1966 through May 1968. (DCSO records Vol. 35, Pg.14386)

Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 1 in. dia., 28 ins. in the ground, with brass cap mkd:

$\frac{1}{4}$
S 34 | S 35
1966
1955

from which

A Fir 12" dia., bears S.11°E., 5 lks. dist., mkd. $\frac{1}{4}$ S35 BT.

A Fir 18" dia., bears S.54 $\frac{1}{2}$ °W., 20 lks. dist., mkd. $\frac{1}{4}$ S34 BT.

From this point, the point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, established in 1955, bears N.18°47'W., 0.525 chs. dist. Destroyed all marks on the 1955 bearing trees.

Fd. Ok by M. Heimburger, May 2005 - M146-22

continued next page

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Adam DeGroot - For: Silver Butte Timber Co. - Dec. 2019 - M171-74

Found - A 1" USBLM IP by Jelley in 1966, firmly set and projecting 8" above ground with a 2½" brass cap properly mkd. From which

A 1966 BT, a 25" D.Fir bears S.53°15'W., 13.8 ft w/healed blaze (S.54½°W., 20 lks)

New BTs- A 26" D.Fir bears N.46°45'E., 40.7 ft scribed "¼ S35 BT" on dbl blaze

A 24" D.Fir bears S.17°45'E., 19.4 ft scribed "¼ S35 BT" on dbl blaze

A 39" D.Fir bears N.49°45'W., 47.6 ft scribed "¼ S34 BT" on dbl blaze

Note - Corner falls in the 2019 mile post 97 fire scar. All BTs are living with charred bark.

Lat: 42°49'59.04019"N Long: 123°16'03.40011"W