

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - W.H. Byars, under contract # 456 surveyed July 28, 1882 (DCSO rec. Vol. 19 Page 7904)

-
- Set a basalt stone, 14x10x5 ins., 10" in ground, marked with one notch on the South and two notches on the East angles of the same corner to sections 26, 27, 34 and 35, from which
- A Live Oak 5" dia., bears N.18°E., 30 lks. marked T31S R5W S26 BT.
 - A Laurel 12" dia., bears S.25°E., 27 lks. marked T31S R5W S35 BT.
 - A Laurel 5" dia., bears S.23°W., 3 lks. marked T31S R5W S34 BT.
 - A Laurel 12" dia., bears N.20°W., 15 lks. marked T31S R5W S27 BT.

GLO resurvey by Hans W. Thielsen, under Group #320, Surveyed, Oct./Nov. 1955 - (DCSO records Vol. 28 Page(s) 11788)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 1 in. dia., 30 ins. in the ground, with brass cap mkd:

T 31 S R 5 W
<u>S 27 S 26</u>
S 34 S 35
1955

- from which
- A Red Fir 10" dia., bears N.48°E., 24 lks. dist., marked T31S R5W S26 BT.
 - A White Fir 5" dia., bears S.72°E., 17 lks. dist., marked T31S R5W S35 BT.
 - A White Fir 10" dia., bears S.86¼°W., 20 lks. dist., marked T31S R5W S34 BT.
 - A White Fir 4" dia., bears N.30°W., 34 lks. dist., marked T31S R5W S27 BT.

BLM Corrective Resurvey - John Jelley, Lynn Roseberry, Floyd Brooks, Under Group #s 320 and 614, - Surveyed June 1966 through May 1968. (DCSO records Vol. 35 Page(s) 14386)

Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36" long, 2" dia., 28" in the ground with brass cap marked:

T 31 S R 5 W
<u>S 27 S 26</u>
S 34 S 35
1966
1955

(Cont. Next Page)

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 26, 27, 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which

A Fir 15" dia., bears N.46°E., 45 lks. dist., marked T31S R5W S26 BT.

A Fir 11" dia., bears S.68½°E., 33 lks. dist., marked T31S R5W S35 BT.

A Live Oak 8" dia., bears S.76½°W., 17 lks. dist., marked T31S R5W S34 BT.

A Fir 10" dia., bears N.82°W., 61 lks. dist., marked T31S R5W S27 BT.

From this point, the point for the cor. of 26, 27, 34 and 35, established in 1955, bears N.18°47'W., 1.05 chs. dist. Destroyed all marks on the 1955 bearing trees.