

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Pages 7905-06)

-----  
Set a Fir post, 3 ft. long, 3" square, 18" in ground, marked ¼ S on West side, for the ¼ sec. cor., from which  
A Fir 15" dia., bears N.70°E., 20 lks. dist., mkd ¼ S BT.  
A Fir 14" dia., bears S.75°W., 45 lks. dist., mkd ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones and Joe Brady - May/June 1966 - C.S. file 54/25-17

-----  
Found - 14" D.Fir now 24", tree dead, S.75°W., 29.7 ft. Very faint bark scribe "S". Other marks not legible.  
15" Fir N.70°E., 13.2 ft. No Trace.

Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 5 W  
¼ S 27 | S 26  
1966

New BTs -10" D.Fir N.69½°W., 5.4 ft. scribed ¼ S27 CS BT.  
12" Yew N.32°E., 35.2 ft. scribed ¼ S26 CS BT.

This corner lies South of ridge, 90.0 ft.

BLM Corrective Resurvey - John Jelley, Lynn Roseberry, Floyd Brooks, Under Group #s 320 and 614, - Surveyed June 1966 through May 1968. (DCSO records Vol. 35 Page(s) 14388)

-----  
Found ¼ corner, monumented with an iron post, 1" dia., firmly set by Powell in 1966, protruding 8" above ground, with brass cap marked: COUNTY SURVEYORS OFFICE

T 31 S  
R 5 W  
¼ S 27 | S 26  
1966

from which the remaining original bearing tree

A Fir snag, 24" dia., bears S.75°W., 45 lks. dist., with scribe marks S BT faintly visible on badly weathered bark blaze.

and bearing trees marked by Powell

A Yew 12" dia., bears N.32°E., 53 lks. dist., with scribe marks ¼ S26 CS BT visible on open double blaze.

A Fir 10" dia., bears N.69½°W., 8½ lks. dist., with scribe marks ¼ S27 CS BT visible on open double blaze.

Fd. ok by M. Heimbürger, 8/2005 - M148-36