

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Pages 7907-08)

Set a stone, 14x12x6 ins., 10" in the ground with 3 notches on the South and 2 notches on East angles of same for the cor. to secs. 14, 15, 22 and 23, from which

A Laurel 4" dia., bears N.5°E., 20 lks. marked T31S R5W S14 BT.

A Laurel 5" dia., bears S.65°E., 24 lks. marked T31S R5W S23 BT.

A Fir 6" dia., bears S.50°W., 35 lks. marked T31S R5W S22 BT.

A Live Oak 6" dia., bears N.25°W., 50 lks. marked T31S R5W S15 BT.

Victor S. King, Witness: Chester C. Jones - For: Bate Lumber Co. Merlin, OR - Feb. 5, 1959 - C.S. File 42/425-5

Found - Orig. 14" Live Oak N.25°W., 50 lks.

Orig. 9" madrona N.05°E., 20 lks.

Orig. 32" Fir S.50°W., 35 lks.

The Madrona shows scribing. The Oak and Fir have not been chopped into, but show the scars of old blazes.

Set 1¼" Iron pipe 36" long in a mound of stones from which I set the following new bearing trees:

10" Sugar Pine N.10°E., 32.0 ft. scribed T31 R5 S14 BT.

15" Fir S.49°E., 28.7 ft. scribed T31 R5 S23 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones and Joe Brady - May 1966 - C.S. File 54/25-6

Found - 1½" Iron pipe at sec. corner.

Orig. 14" L.Oak N.25°W., 33.0 ft. shows good scar.

Orig. 9" Laurel N.5°E., 13.2 ft Tree has rotten face

Orig. 32" D.Fir now 35" S.50°W., 23.1 ft. shows good scar.

10" S.Pine N.10°E., 32.0 ft. Tree now dead, scribe visible, BT.

15" D.Fir now 18" S.49°E., 28.7 ft. good scar.

New BT - 8" Laurel N.7°E., 15.1 ft. scribed T31S R5W S14 CS BT.

Also at corner is 4" x 4" white post marked SW Cor. of Cl.#8.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15673-74)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

The Sec. Cor., perpetuated and recorded by King, RLS #442 in 1959, further perpetuated and recorded by Powell in 1966, monumented with an iron pipe, 1½" dia., firmly set, protruding 8" above ground, from which the remains of the original bearing trees:

A Madrone 9" dia., bears N.5°E., 20 lks., no marks visible on decayed blaze.

A Fir 35" dia., bears S.50°W., 35 lks., with healed blaze.

A Live Oak 14" dia., bears N.25°W., 50 lks., with healed blaze.

and bearing trees mkd. by King:

A Sugar Pine snag, 10" dia., bears N.10°E., 49 lks., with scribe marks T31S R5W S14 BT visible on open blaze.

A Fir 19" dia., bears S.49°E., 43 lks., with healed blaze.

and bearing tree mkd. by Powell:

A Madrone 9" dia., bears N.7°E., 23 lks., with scribe marks T31S R5W S14 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. dia., 22 ins. in the ground, with brass cap mkd:

T	31	S	R	5	W
	S	15		S	14
	S	22		S	23
				1972	

Deposit Iron pipe alongside iron post.

Fd. OK, by Bruce Shaner, June 1992, M 112-49

Ron Quimby - Crew: N. Fromdahl & J. Ogden - 9/2019 - C.S.
 File 65/104-10

Found - 1972 BLM brass cap (properly mkd)
 12" dead madrona (burnt) N.5°E., 13.2 ft. healed scar.

Remains of Fir stump S.50°W., 23.1 ft.

Remains of Fir stump S.49°E., 28.4 ft.

12" dead madrona (burnt) N.7°E., 15.2 ft.

New - 5/8"x30" I.Rod with yellow cap "ie engineering"
 N.89°E., 5.0 ft.

5/8"x30" I.Rod with yellow cap "ie engineering"
 S.47°E., 5.0 ft.

5/8"x30" I.Rod with yellow cap "ie engineering"
 S.41°W., 6.0 ft.

5/8"x30" I.Rod with yellow cap "ie engineering"
 N.31°W., 8.0 ft.

Note - Area burnt badly 2019
 Compass decl. 15½°E.