TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 surveydated July 28, 1882 (DCSO rec. Vol. 19 Page 7911)

Set a basalt stone, 20x12x8 ins., 15" in ground, marked ¼ on W. side for the ¼ sec. cor., from which
A Live Oak 15" dia., bears N.62°E., 125 lks. mkd. ¼ S BT.
A Fir 26" dia.,bears N.63°W.,164 lks. dist., mkd. ¼ S BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15679)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. dia., 8 ins. in the ground to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd: ¼

S 10 | S 11
T 31 S R 5 W
1973

from which
A White Oak 16" dia., bears S.35½°E., 81½ lks. dist., mkd. ¼ S11 BT.
A Live Oak 13" dia., bears N.44½°W., 65 lks. dist., mkd. ¼ S10 BT.

Ron Quimby - Crew: N. Fromdahl & L. Heddens - 2/2020 - C.S. File 65/104-57

Found - BLM brass cap (properly mkd)
Orig. BTs burnt
New - ⅝"x30" I.Rod N.15°E., 5.0 ft.
⅝"x30" I.Rod S.56°E., 7.0 ft.
⅝"x30" I.Rod N.35°W., 7.0 ft.
⅝"x30" I.Rod S.45°W., 6.0 ft.
All rods have yellow plastic cap stamped "ie engineering". 5' Alum. post alongside I.Rods.
Note - Area badly burnt 2019
Compass decl. 15½°E.