TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7913)

Set a Laurel post, 3 ft. long, 3" dia., 18" in ground, marked ¼ S on West face for the ¼ sec. cor., from which
A Laurel 14" dia., bears S.65°E., 30 lks. mkd. ¼ S BT.
A Laurel 17" dia., bears N.35°W., 5 lks. mkd. ¼ S BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15681-82)

Point for the ¼ sec. cor. at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. dia., 22 ins. in the ground, with brass cap mkd: T 31 S R 5 w

¼
S 3 | S 2
1973

from which
A Fir 22" dia., bears N.74¼°E., 75 lks., mkd. ¼ S2 BT.
A Fir 32" dia., bears S.73¼°W., 75 lks., mkd. ¼ S3 BT.

BLM dependent resurvey by Markell G Hamm, Cadastral Surveyors, under Group #2927, surveyed June/Sept. 2017 - (DCSO records Vol. 59 Page(s) 23724-5)

The ¼ sec. cor. of secs. 2 & 3, reported by Berry & Akin in 1973, monumented with an iron post, 2½" dia., firmly set, projecting 7" above ground, with a brass cap properly mkd. from which the bearing trees reported by Berry and Akin
A fir, 28" dia., bears N.74¼°E., 49.5 ft., with a healed blaze, and axe marks visible in bark.
A fir, 36" dia., bears S.71¼°W., 47.9 ft., with a healed blaze, and axe marks visible in bark. (Record, S.73¼°W., 49.5 ft.)
Corner is located on moderate S. slope with mature fir and heavy poison oak.
NAD 1983 (2011)
Latitude: 42°54'15.74"N. Longitude: 123°15'59.09"W.