

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 dated July 28, 1882 (DCSO rec. Vol. 17 Page 7162)

-----  
Set a stone 18" x 12" x 6" 12" in the ground for the cor. to secs. 2, 3, 34 and 35 mkd. with two notches on the east angle and 4 notches on the west angle of same and, from which  
A Fir 12" dia., bears N.12°E., 64 lks. dist. mkd.  
T30S R5W S35 BT.  
A Fir 10" dia., bears S.54°E., 72 lks. dist., mkd.  
T31S R5W S2 BT.  
A live Oak 10" dia., bears S.28°W., 9 lks. dist., mkd.  
T31S R5W S3 BT.  
A Fir 15" dia., bears N.26°W., 14 lks. dist., mkd.  
T30S R5W S34 BT.

Victor S. King, L.S. #442 - For: Bate Lumber Co. - April 8, 1959 - C.S. File 42/425-9

-----  
Found - Mound of stones and 4" sq. post.  
Orig. BT, 26" Fir scribed in bark rescribed in bark  
S34 T30S R5W BT, N.26°W. 9.2 ft.  
18" Live Oak, blown down. (Scribed)  
18" Fir, orig. BT, rescribed in bark S2 T31S R5W BT,  
S.54°E., 45.7 ft.  
New BTs -6" Fir S.22°W., 30.9 ft. scribed S3 T31S R5W BT.  
24" Fir N.15°E., 42.6 ft. scribed S35 T30S R5W BT in  
bark.  
Rescribed the 2 orig. BTs as noted above.

Doug. County Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman - Nov. 1963 - C.S. File 53/26-36

-----  
Found - Squared stake and mound of stone at corner and bearing trees as recorded in 1959.  
Set Brass cap at cor. mkd. County Surveyor's S34 | S35 T30S  
Office 1963 S 3 | S 2 T31S R5W  
No new bearing trees.

BLM resurvey by Jelley, Roseberry, and Brooks, under Group #'s 320 and 614 - Surveyed June 1966/May 1968 (DCSO records, Vol. 35 Pages 14359-60)

-----  
The cor. of secs. 2 and 3 only on the N. bdy. of the Tp. established by Byars in 1882, perpetuated and recorded by  
(Cont. Next Page)

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 and 3 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

V.S. King in 1959, again perpetuated and recorded by Byron in 1963, monumented with an iron post, 1" dia., protruding 16" above ground, firmly set with brass cap mkd. COUNTY SURVEYORS OFFICE T30S R5W S34 S35 S3 S2 T31S 1963, from which the original bearing trees:

A Fir 27" dia., bears N.14°E., 64 lks. dist., with illegible scribe marks visible on bark blaze. Remarked S35 T30S R5W BT on the bark by King in 1959. (Rec. N.12°E.)

A Fir 18" dia., bears S.54°E., 65 lks. dist., with no marks visible. Remarked S2 T31S R5W BT on the bark by King in 1959. (Rec. 72 lks.)

A root hole bears S.28°W., 9 lks. dist., alongside of which is a fallen live Oak 18" dia., with illegible scribe marks visible on rotted blaze.

A Fir 30" dia., bears N.26°W., 16 lks., with illegible scribe marks visible on bark blaze. Remarked S34 T30S R5W BT on the bark by King in 1959 (Rec 14 lks)

and a bearing tree mkd. by King in 1959

A Fir 10" dia., bears S.21½°W., 47 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd:

T 30 S R 5 W  
S 35  
-----  
S 3 | S 2  
T 31 S R 5 W  
1967

Deposit local iron post inverted alongside the iron post.

Fd. Corner OK, BLM resurvey by Berry and Akin, 1972-73 under Group #800 (DCSO records, Vol. 38 Page 15656)

Douglas Co. Surveyors Office - Stephen Flause - Mike Koch - Feb. 20, 2013, filed 12/5/2018 - C.S. File 67/45-13

-----  
Monument and accessories fd ok.  
Accessories are re-tagged and re-flagged as necessary.  
Dec. 15½°E

BLM dependent resurvey by Markell G Hamm, Cadastral Surveyors, under Group #2927, surveyed June/Sept. 2017 - (DCSO records Vol. 59 Page(s) 23726)

-----  
The cor. of secs. 2 & 3 only, on the N. bdy. of the Tp., reported by Berry & Akin in 1972-73, monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with a brass cap (properly) mkd. continued next page

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

from which the bearing trees reported by Berry and Akin  
A fir, 32" dia., bears N.14°E., 42.2 ft., with scribe marks S35 T30S R5W BT visible on bark. (Original)  
A fir, 22" dia., bears S.54°E., 42.9 ft., with a healed blaze. (Original)  
A fir, 15" dia., bears S.21½°W., 31.0 ft., with a healed blaze.  
A fir, 33" dia., bears N.26°W., 10.6 ft., with scribe marks S34 T30S R5W BT visible on bark. (Original)  
NAD 1983 (2011)  
Latitude: 42°54'41.90" N Longitude: 123°15'23.10" W