

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 539700

PRIMARY CORNER DESCRIPTION S. 1/4 Cor. Sec. 35 only, T30-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7133)

Set ¼ sec. post at proper distance, from which
A R.Fir 12" dia., bears S.34°W., 63 lks. dist.
A R.Fir 18" dia., bears N.43°E., 28 lks. dist.

BLM resurvey by Jelley, Roseberry, and Brooks, under Group #'s 320 and 614 - Surveyed June 1966/May 1968 (DCSO records, Vol. 35 Page 14358)

Point for the ¼ sec. cor. of sec. 35 only, on the S bdy. of T.30S R5W, at proportionate distance, based on the 1854 Ford record. There is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 30 S R 5 W
¼ S 35
1967

from which

A Fir 15" dia., bears N.7¼°E., 124 lks. dist., mkd.
¼ S35 BT.
A Fir 33" dia., bears N.39°W., 76 lks. dist., mkd.
¼ S35 BT.

Corner Fd. OK, by BLM resurvey by Berry and Akin in 1972-73 under Group #800 (DCSO records, Vol. 38 Page 15655)