

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; & Sec. 2, T32-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Geo. W. Hyde, under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7882)

Set ¼ sec. post on W. slope, from which
A Maple 9" dia., bears N.18°W., 9 lks. dist.
A Dogwood 8" dia., bears S.33°30'E., 11 lks. dist.

BLM resurvey by Hans W. Thielsen under Group #320, Surveyed, Oct/Nov. 1955 (DCSO records Vol. 28 Page(s) 11784)

Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36" long, 1" dia., 30" in the ground, with brass cap marked:

$$\frac{1}{4} \frac{S}{S} \frac{35}{2}$$

1955

from which

A Maple 12" dia., bears N.12°E., 119 lks. dist., marked ¼ S35 BT.
A Cedar 8" dia., bears S.54°E., 106 lks. dist., marked ¼ S2 BT.

Fd. by G.Nygren 8/2000 M135-46

DCSO-GIS Corner visitation - 1/21/2004 - Typed: 2/10/2011 - C.S. File 67/33-1

Monument - 1" IP/BC
Comment - needs rehab

Fd. Ok by M. Heimbürger, May 2005 - M146-22