

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 surveyed July 28, 1882 (DCSO rec. Vol. 19 Page 7907)

Set a basalt stone 14x13x6 ins., 10" in ground, marked $\frac{1}{4}$ on N. side for the $\frac{1}{4}$ sec. corner, from which
A Live Oak 7" dia., bears S.25°W., 20 lks. marked $\frac{1}{4}$ S BT.
A Live Oak 8" dia., bears N.28°W., 16 lks. marked $\frac{1}{4}$ S BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15671)

Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. dia., 22 ins. in the ground, with brass cap mkd: T 31 S R 5 W

$\frac{1}{4}$ $\frac{S\ 23}{S\ 26}$
1973

from which

A Fir 15" dia., bears N.7 $\frac{1}{2}$ °E., 34 lks. dist. mkd. $\frac{1}{4}$ S23 BT.

A Fir 12" dia., bears S.18 $\frac{1}{2}$ °W., 32 lks. dist. mkd. $\frac{1}{4}$ S26 BT.

Fd. ok by M. Heimbürger, 8/2005 - M148-36