

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 surveyed July 28, 1882 (DCSO rec. Vol. 19 Page 7910)

-----  
Set a basalt stone, 14x12x12 ins., 10" in ground, marked ¼ S on North side for the ¼ sec.cor., from which

A Fir 18" dia., bears N.22°E., 20 lks. dist., mkd. ¼ S BT.

A Fir 28" dia., bears S.30°E., 42 lks. dist., mkd. ¼ S BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15678)

-----  
Point for the ¼ sec. cor. at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. dia., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd: T 31 S R 5 W

¼ S 11  
S 14

1973

from which

A Fir 8" dia., bears N.23°E., 49 lks. dist., mkd. ¼ S11 BT.

A Fir 28" dia., bears S.2°W., 97 lks. dist., mkd. ¼ S14 BT.