TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7912)

Set Laurel post 3 ft. long, 3" square, 18" in ground, marked ¼ S on N. face for the ¼ sec. cor., from which
A Laurel 7' dia., bears S.70°E., 8 lks. mkd. ¼ S BT.
A Fir 14" dia., bears N.5°W., 24 lks. dist. mkd. ¼ S BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15681)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. dia., 24 ins. in the ground, with brass cap mkd: ¼ S 2 / S 11 T 31 S R 5 W 1973
from which
A Double Fir 50" dia., bears N.27°E., 22 lks. mkd. ¼ S2 BT
A Fir 23" dia., bears S.28° W., 100 lks., mkd. ¼ S11 BT

BLM dependent resurvey by Markell G Hamm, Cadastral Surveyors, under Group #2927, surveyed June/Sept. 2017 - (DCSO records Vol. 59 Page(s) 23723-4)

The ¼ sec. cor. of secs. 2 & 11, reported by Berry and Akin in 1973; monumented with an iron post, 2½" dia., firmly set, projecting 7" above ground, with a brass cap (properly) mkd. from which the bearing trees reported by Berry and Akin
A double trunk fir, 57" dia., bears N.28°E., 13.8 ft., with a healed blaze. (Record, N.27°E., 14.5 ft.)
A fir, 42" dia., bears S.29½°W., 62.8 ft., with a healed blaze. (Record, S.28°W., 66.0 ft.)
Corner is located on moderate S. slope with mature fir and some undergrowth.

Ron Quimby - Crew: N. Fromdahl & L. Heddens - 2/2020 - C.S. File 65/104-58

Found - BLM brass cap (properly mkd)
58" Double trunk fir N.28°E., 13.8 ft. (healed scar)
42" Fir S.29½°W., 62.8 ft. (good scar)
New - 5' alum. Post 5.0 ft. North & 5.0 ft. West
Note - Area badly burnt 2019
Compass decl. 15½°E.