

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 2

Alias	Description

BLM dependent resurvey by Markell G Hamm, Cadastral Surveyors, under Group #2927, surveyed June/Sept. 2017 - (DCSO records Vol. 59 Page(s) 23727)

Point for the center ¼ sec. cor. of sec. 2, at intersection with the E. and W. center line.
Set a stainless steel post, 28" long, 2½" dia., 12" in the ground, in a mound of stone, 3 ft. base, to the top, with brass cap mkd.

T31S R5W
C ¼ S 2
2018

from which

A pine, 9" dia., bears S.28°E., 38.7 ft., mkd. S2 C¼ BT.
A madrone, 5" dia., bears N.53¼°W., 38.3 ft, mkd C¼ S2 BT.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

Ron Quimby - Crew: R. Heichel & J. Ogden - 2/2020 - C.S. File 65/104-59

Found - BLM brass cap (properly mkd)
9" Pine S.28°E., 38.7 ft. (burnt)
5" Madrone N.53¼°W., 38.3 ft. (burnt)
New - ⅝"x30" I.Rod North 12.0 ft.
⅝"x30" I.Rod South 7.0 ft.
5' alum. Post alongside of I. Rods
Both have yellow plastic cap stamped "ie engineering". Alum. post alongside.
Note - Area badly burnt 2019
Compass decl. 15½°E.