

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 surveyed July 28, 1882 (DCSO rec. Vol. 19 Page 7892-93)

-----  
Set a Fir post, 4 ft. long, 3" square, 20" in ground, marked 1/4 S on the W. side for the 1/4 sec.cor., from which

A Fir 12" dia., bears S.78°E., 14 lks. dist., marked 1/4 S BT.

A Fir 36" dia., bears S.72°W., 65 lks. dist., marked 1/4 S BT.

-----  
GLO resurvey by Hans W. Thielsen, under Group #320, Surveyed, Oct./Nov. 1955 - (DCSO records Vol. 28 Page(s) 11786)

-----  
Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36" long, 1" dia., 30" in the ground, with brass cap marked:

1/4  
S35|S36  
1955

from which

A Red Fir 12" dia., bears S.80°E., 130 lks. dist., marked 1/4 S36 BT.

A Red Fir 14" dia., bears N.79°W., 31 lks. dist., marked 1/4 S35 BT.

-----  
Fd. Ok by M. Heimbürger, May 2005 - M146-22