

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7893)

Set a fir post, 4 ft. long, 4" square, 20" in ground, marked T31S R5W S25 on the NE. side, S36 on the SE. side, S35 on the SW. side and S26 on the NW. side. Also made one notch on S. and E. angles of the same for the cor. to secs. 25, 26, 35 and 36, from which

- A Laurel 8" dia., bears N.63°E., 9 lks. dist., marked T31S R5W S25 BT.
- A Fir 6" dia., bears S.35°E., 29 lks. dist., marked T31S R5W S36 BT.
- A Laurel 7" dia., bears S.26°W., 39 lks. dist., marked T31S R5W S35 BT.
- A Laurel 5" dia., bears N.81°W., 25 lks. dist., marked T31S R5W S26 BT.

GLO resurvey by Hans W. Thielsen, under Group #320, Surveyed, Oct./Nov. 1955 - (DCSO records Vol. 28 Page(s) 11787)

The cor. of secs. 25, 26, 35 and 36, determined at record bearing and distance from the original SE. bearing tree:

- A turned-out Fir, 24" dia., bears S.35°E., 29 lks. dist., with marks BT uncovered.

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd:

T 31	S R 5 W
S 26	S 25
S 35	S 36
1955	

from which new bearing trees:

- A Red Fir 24" dia., bears N.47°E., 6 lks. dist., marked T31S R5W S25 BT.
- A Red Fir 32" dia., bears S.51°E., 55 lks. dist., marked T31S R5W S36 BT.
- A Red Fir 32" dia., bears S.62½°W., 111 lks. dist., marked T31S R5W S35 BT.
- A Red Fir 23" dia., bears N.43½°W. 27 lks. dist., marked T31S R5W S26 BT.

Douglas Co. Surveyors Office - John Powell and Crew - Sept. 11, 1969 - C.S. File 54/25-16

Found - GLO brass cap properly mkd., set in 1955.
24" D.Fir, now dead, N.47°E., 4.0 ft. pitched over, scribe visible.
32" D.Fir, now 32", S.51°E., 36.3 ft. pitched over, scribe visible. (Cont. Next Page)

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

32" D.Fir, now dead, S.62½°W., 73.6 ft. pitched over, scribe visible.
23" now 29" D.Fir, N.43½°W., 17.8 ft. pitched over, scribe visible.
New BTs -10" Hemlock N.73°E., 43.6 ft. mkd: T31S R5W S25 CS BT.
12" Maple S.55°W., 80.6 ft. mkd: T31S R5W S35 CS BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15657-58)

The Sec. cor., monumented with an iron post, 2" dia., protruding 6" above ground, with brass cap mkd: T 31 S R 5 W
S 26 | S 25
S 35 | S 36
1955

from which bearing trees mkd. by Thielsen:
A sawed Fir stump, 26" dia., bears N.47°E., 6 lks. dist., with illegible scribe marks visible on open blaze.
A Fir 39" dia., bears S.51°E., 55 lks. dist., with healed blaze.
A sawed Fir stump, 32" dia., bears S.62½°W., 111 lks. dist., with healed blaze.
A sawed Fir stump, 24" dia., bears N.43½°W., 27 lks. dist., with healed blaze.
and bearing trees mkd. by the County:
A Hemlock 10" dia., bears N.73°E., 65 lks. dist., with healed blaze.
A Maple 12" dia., bears S.54°W., 121 lks. dist., with scribe marks T31S R5W S35 BT visible on open blaze.
and a new bearing tree:
A Fir 16" dia., bears N.43 3/4°W., 215 lks. dist., mkd. T31S R5W S26 BT.

Fd. Ok by M. Heimbürger, May 2005 - M146-22