TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 25 and 26

Alias Description
Alias Description
Alias Description
Alias Description

Original - W.H. Byars, under contract # 456 surveydated July 28, 1882 (DCSO rec. Vol. 19 Page 7895)

Set a Laurel post, 3 ft. long, 3" dia., 18" in ground, marked ¼ S on the W. face, from which
A Fir 12" dia., bears S.5°E., 65 lks. dist., marked ¼ S BT.
A Fir 12" dia., bears West, 27 lks. dist., marked ¼ S BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15658)

Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 31 S R 5 W

¼
S 26|S 25
1973

from which
A Fir 25" dia., bears S.41½°E., 58 lks., marked ¼ S25 BT.
A Fir 25" dia., bears N.17°W., 33½ lks. marked ¼ S26 BT.

Fd. ok by M. Heimburger, 8/2005 - M148-36