

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Pages 7896-97)

Set a basalt stone 18x13x12 ins., 12" in ground, marked ¼ on West side for the ¼ sec. cor., from which

A Laurel 12" dia., bears S.40°E., 40 lks. dist., marked ¼ S BT.

A Fir 14" dia., bears S.70°W., 23 lks. dist., marked ¼ S BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15661)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ in. diam., 24 ins. in the ground, with brass cap mkd: ¼

S 23 S 24

T 31 S R 5 W

1973

from which

A Fir 17" dia., bears N.58°E., 51½ lks. dist., mkd. ¼ S24 BT.

A Fir 18" dia., bears N.26°W., 28 lks. dist., marked ¼ S23 BT.

Found OK, Feb. 1996 by G. Lang - M 127-73