

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 surveyed July 28, 1882 (DCSO rec. Vol. 19 Pages 7898-99)

-----  
Set a Fir post, 3 ft. long, 3" square, 20" in ground, marked ¼ S on West side for the ¼ sec. cor., from which  
A Laurel 10" dia., bears S.65°E., 9 lks. dist., marked ¼ S BT.  
A Fir 10" dia., bears S.55°W., 14 lks. dist., marked ¼ S BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15664)

-----  
Point for the ¼ sec cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd: ¼  
S 14 S 13  
T 31 S R 5 W  
1973

from which  
A Fir 11" dia., bears N.70°E., 38 lks. dist., mkd. ¼ S13 BT.  
A Fir 10" dia., bears N.67°W., 21 lks. dist., mkd. ¼ S14 BT.