

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - W.H. Byars, under contract # 456 surveyed July 28, 1882 (DCSO rec. Vol. 19 Page 7899)

Set a stone 14x12x7 ins., 10" in ground, marked with 4 notches on the S. and one notch on the E. angles of same for the cor. to secs. 11, 12, 13 and 14, from which

- A Laurel 12" dia., bears N.55°E., 32 lks. dist., marked T31S R5W S12 BT.
- A Fir 15" dia., bears S.30°E., 26 lks. dist., marked T31S R5W S13 BT.
- A Fir 15" dia., bears S.63°W., 48 lks. dist., marked T31S R5W S14 BT.
- A Fir 16" dia., bears N.78°W., 49 lks. dist., marked T31S R5W S11 BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15664-65)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd: T 31 S R 5 W

S 11 S 12
S 14 S 13
1973

from which

- A Fir 15" dia., bears N.66½°E., 3 lks. dist., mkd. T31S R5W S12 BT.
- A Fir 8" dia., bears S.13½°E., 22 lks. dist., mkd. T31S R5W S13 BT.
- A Fir 17" dia., bears S.48°W., 23 lks. dist., mkd. T31S R5W S14 BT.
- A Fir 7" dia., bears N.22°W., 35 lks. dist., mkd. T31S R5W S11 BT.