

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7900)

-----  
Deposited a basalt stone 15x8x6 ins., 12" in ground for ¼ sec. cor., marked ¼ S on West side, from which

A Laurel 14" dia., bears S.15°E., 41 lks. marked ¼ S BT.

A Cedar 10' dia., bears S.10°E., 41 lks. marked ¼ S BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15667)

-----  
Point for the ¼ sec. cor. of sec. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. dia., 24 ins. in the ground, with brass cap mkd:

S 11 | S 12  
T 31 S R 5 W  
1973

from which

A Fir 17" dia., bears S.22½°E., 57½ lks. dist., mkd. ¼ S12 BT.

A Fir 12" dia., bears N.29½°W., 44 lks. dist., mkd. ¼ S11 BT.

Bruce Shaner - July 2000 - M 132-51 & C. S. File 65/33-1B

-----  
Found - ¾" brass cap on a 2½" iron post, from which:  
26" (rec. 17") D.Fir BT, face overgrown, bears S.22½°E., 38.0 ft.

18" (rec. 12") D.Fir BT stump, face overgrown, bears N.29½°W., 29.0 ft.

New BT - 6" D.Fir BT, I scribed "¼ S11 BT" bears N.48½°W., 34.1 ft.

Gerald Nygren - For: Douglas Co. Land Dept - 3/2020 - M176-80

-----  
Found - 1973 BLM brass cap  
17" D.Fir now 27" bears S.22°30'E., 38.0' healed blaze. 1973

12" D.Fir now burnt stump hole, bears N.29°30'W., 29.0'. 1973

6" D.Fir now 11" bears N.48°30'W., 34.1' healed blaze. 1973

Set - 5.5' metal post, east 5.0'