TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. For Secs. 1 and 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 surveydated July 28, 1882 (DCSO rec. Vol. 19 Page 7903)

Set a basalt stone, 15x15x6 ins., 10" in ground for the ¼ sec. cor., marked ¼ on West face of the same, from which

A Maple 12" dia., bears S.80°E., 24 lks. dist. marked ¼ S BT.

A Fir 24" dia., bears S.80°W., 74 lks. dist., marked ¼ S BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15670)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. dia., 22 ins. in the ground, with brass cap mkd: T 31 S R 5 W

¼
S 2 | S 1
1973

from which

A Fir 20" dia., bears N.72°E., 46 lks. dist., mkd. ¼ S1 BT

A Fir 18" dia., bears S.14½°W., 92½ lks. dist., mkd. ¼ S2 BT.

BLM dependent resurvey by Markell G Hamm, Cadastral Surveyors, under Group #2927, surveyed June/Sept. 2017 - (DCSO records Vol. 59 Page(s) 23728)

The ¼ sec. cor. of secs. 1 and 2, reported by Berry & Akin in 1973, monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd. from which the remains of the BT reported by Berry and Akin

A shattered fir stump, 23" dia., bears N.72°E., 30.4 ft., with scribe marks ¼ S1 BT visible on partially healed blaze, downhill of which is the remainder of the tree.

and new bearing trees

A fir, 31" dia., bears S.64¾°E., 47.9 ft., mkd. ¼ S1 BT.

A fir, 15" dia., bears S.13¾°W., 72.2 ft., mkd. ¼ S2 BT.

Corner is located on steep SW shale slope, with maple, fir, laurel, and poison oak.