

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 36; 1 T32-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Geo. W. Hyde, under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7881)

-----  
Set ¼ post on W slope, from which  
A maple, 9" dia., bears N.18°W., 9 lks.  
A dogwood, 8" dia., bears S.33°30'E., 11 lks.

BLM Dependent resurvey by Arthur R. Rambo, Cadastral Surveyor under Group No. 2707, surveyed April/May 2013 - (DCSO records, Vol. 58 Page(s) 23127)

-----  
Point for the ¼ sec. cor. of secs. 1 & 36, on the N. bdy. of the Tp., at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28" long, 22" in the ground, in a collar of stone, with brass cap mkd.

T 31 S R 5 W

¼  $\frac{S\ 36}{S\ 1}$

T 32 S

2013

from which

A cedar, 10" dia., bears N.1¾°E., 3.5 ft., mkd. ¼ S36 BT.

A fir, 13" dia., bears S.34¼°E., 22.0 ft., mkd. ¼ S1 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Ron Quimby - Crew: N. Fromdahl, & R. Olson - 11/2015 - C.S. File 65/95-3

-----  
Found - BLM brass cap  
10" Cedar N.2°E., 3.5' open scribes  
13" fir S.34°E., 22.0' partially healed scribes.

New - 5" Fir N.36°E., 16.8' scribed ¼ S36 BT.  
10" Cedar S.34°W., 11.9' scribed ¼ S1 BT.

Note - Corner is approx. 150' west of end of road.  
Hand held Lat & Long.

N. 42°49.566  
W. 123°14.296