

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 surveyed July 28, 1882 (DCSO rec. Vol. 19 Page 7894)

Set a stone 12x12x5 ins., 10" in ground, marked $\frac{1}{4}$ S on the N. side, for the $\frac{1}{4}$ sec. cor., from which

A Maple 12" dia., bears N., 50 lks. dist., marked $\frac{1}{4}$ S BT.

A Fir 7" dia., bears S.35°E., 24 lks. dist., marked $\frac{1}{4}$ S BT

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15657)

Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd: $\frac{1}{4}$ $\frac{S\ 25}{S\ 36}$

T 31 S R 5 W
1973

from which

A Fir 15" dia., bears N.30 $\frac{1}{4}$ °E., 67 $\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S25 BT.

A Fir 11" dia., bears S.87 $\frac{1}{2}$ °W., 22 $\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S36 BT.

Corner is located on spur, slopes N.